

# Timings of common tasks using the **data.table** package in R

Matthew Dowle

Revised: November 28, 2011  
(A later revision may be available on the [homepage](#))

\* WORK IN PROGRESS \*

This document contains a series of tests, followed by a summary table of various timings and comparisons. Please go straight to the summary table first <here> in which each row has a link back to the test.

This document is reproducible. Simply run the .Rnw file yourself in your environment to confirm the results. Also see ?vignette, which says that edit(vignette("datatable-timings")) will extract the code from this document so you can easily work with it.

The .Rnw included in the package has N=10,000,000. This is a small number so that 'R CMD build' completes in a reasonable time (about 5 minutes). We don't want the nightly builds on R-Forge and CRAN to slow down just to run long timing comparisons. We have increased this to N=100,000,000 ourselves, and included the output on the datatable homepage (<link>).

## Contents

<b>1 Timing tests</b>	<b>1</b>
1.1 Extraction	1
1.2 Grouping	2
1.3 Test 3	3
1.4 Test 4	3
1.5 Test 5	3
<b>2 Summary table</b>	<b>3</b>

## 1 Timing tests

### 1.1 Extraction

This is a repeat of the test in section 1 of the Introduction vignette. The syntax is explained there. This demonstrates the large difference in speed between vector scans and binary search. Therefore, please avoid using == in the i expression.

```
> n = ceiling(1e7/26^2) # 10 million rows
> DF = data.frame(x=rep(LETTERS,each=26*n),
+                   y=rep(letters,each=n),
+                   v=rnorm(n*26^2))
> DT = data.table(DF,key="x,y")
> tables()

      NAME      NROW  MB COLS KEY
[1,] DT    10,000,068 153 x,y,v x,y
Total: 153MB

> tt=system.time(ans1 <- DF[DF$x=="R" & DF$y=="h",]); tt
```

```

      user  system elapsed
12.545    0.908  13.499

> head(ans1)

      x y      v
6642058 R h  0.9927051
6642059 R h -0.2068228
6642060 R h  1.1520077
6642061 R h -0.1418879
6642062 R h -0.2159998
6642063 R h  0.1045571

> dim(ans1)
[1] 14793      3

> ss=system.time(ans2 <- DT[J("R","h")]); ss

      user  system elapsed
0.028    0.000   0.031

> head(ans2)

      x y      v
[1,] R h  0.9927051
[2,] R h -0.2068228
[3,] R h  1.1520077
[4,] R h -0.1418879
[5,] R h -0.2159998
[6,] R h  0.1045571

> dim(ans2)
[1] 14793      3

> identical(ans1$v,ans2$v)
[1] TRUE

```

## 1.2 Grouping

This is a repeat of the test in section 2 of the Introduction vignette. The syntax is explained there.

```

> ttt=system.time(ans1 <- tapply(DF$v,DF$x,sum)); ttt

      user  system elapsed
16.685    1.001  17.720

> head(ans1)

      A          B          C          D          E
-1330.55024  85.49247 -142.82519 -219.98410 -1612.25545
      F
217.76294

> sss=system.time(ans2 <- DT[,sum(v),by=x]); sss

      user  system elapsed
0.496    0.144   0.637

```

```

> head(ans2)

      x      V1
[1,] A -1330.55024
[2,] B   85.49247
[3,] C  -142.82519
[4,] D  -219.98410
[5,] E -1612.25545
[6,] F   217.76294

> identical(as.vector(ans1), ans2$V1)
[1] TRUE

```

### 1.3 Test 3

### 1.4 Test 4

### 1.5 Test 5

## 2 Summary table

```

> ans

      base data.table times faster
==    13.499     0.031      435
tapply 17.720     0.637       27

> toLatex(sessionInfo())

```

- R version 2.14.0 (2011-10-31), i686-pc-linux-gnu
- Locale: LC\_CTYPE=en\_GB.UTF-8, LC\_NUMERIC=C, LC\_TIME=en\_GB.UTF-8, LC\_COLLATE=C, LC\_MONETARY=en\_GB.UTF-8, LC\_MESSAGES=en\_GB.UTF-8, LC\_PAPER=C, LC\_NAME=C, LC\_ADDRESS=C, LC\_TELEPHONE=C, LC\_MEASUREMENT=en\_GB.UTF-8, LC\_IDENTIFICATION=C
- Base packages: base, datasets, grDevices, graphics, methods, stats, utils
- Other packages: data.table~1.7.4
- Loaded via a namespace (and not attached): tools~2.14.0