

Package ‘DOT’

April 16, 2016

Type Package

Title Render and Export DOT Graphs in R

Version 0.1

Date 2016-04-02

Author E. F. Haghish

Maintainer E. F. Haghish <haghish@imbi.uni-freiburg.de>

Description Renders DOT diagram markup language in R and also provides the possibility to export the graphs in PostScript and SVG (Scalable Vector Graphics) formats. In addition, it supports literate programming packages such as 'knitr' and 'rmarkdown'.

Imports V8 (>= 1.0), tools

Suggests knitr, rmarkdown

NeedsCompilation no

URL <http://haghish.com/dot>

BugReports <http://github.com/haghish/DOT>

Repository CRAN

License MIT + file LICENSE

RoxygenNote 5.0.1

Date/Publication 2016-04-16 04:29:08

R topics documented:

dot 2

Index 4

Description

Graph Description Language (DOT) is a simplified and intuitive plain text graphical language. The `dot()` function renders the DOT markup language in R and also provides the possibility to export the graphs in PostScript and SVG (Scalable Vector Graphics) formats. In addition, it supports literate programming packages such as Knitr and R2HTML. Visit <http://haghigh.com/dot> for downloading examples of creating algorithms and several graphs for Rmarkdown and R HTML to generate dynamic procedural graphs in dynamic documents using the DOT package.

Usage

```
dot(DOT, file = NULL, return = "auto")
```

Arguments

| | |
|--------|---|
| DOT | This argument takes a string containing the DOT script. It is advised to use single quotation mark for the DOT string since the script often includes double quotations which can crash the function. |
| file | defines the file name for exporting the graph. The acceptable file extensions are "ps" for PostScript and "svg" for SVG format (see examples below). |
| return | specifies if PS or SVG script should be printed in R console. The acceptable values are "auto", "cat", "verbatim", and NULL. The default value is "auto" which does not return anything unless the <code>dot()</code> function is called within 'knitr' or 'rmarkdown' packages, which require concatenated graphical script. The "cat" returns concatenated PS or SVG script, printed in multiple lines in the R console. The "verbatim" returns a single string which is assignable to an object. |

Value

By default, the function only renders and loads the DOT plot in RStudio but does not return any PS or SVG script. If the `return` argument is specified, it returns PostScript or SVG script. Note that for assigning the script returned from `dot()` to an object, only "verbatim" value can be used to create a string object.

Author(s)

E. F. Haghigh
Medical Informatics and Biostatistics (IMBI)
University of Freiburg, Germany
<haghigh@imbi.uni-freiburg.de>

Department of Mathematics and Computer Science
University of Southern Denmark
<haghigh@imada.sdu.dk>

Examples

```
#create a simple DOT graph and load it in RStudio
dot("digraph {A -> B;}")

#to produce a dynamic document including a diagram in 'rmarkdown'
## Not run:
```{r echo=FALSE, results='asis'}
library(DOT)
dot("digraph {A -> B;}", return = "cat")
```
## End(Not run)

#create a DOT graph and export a SVG file to the working directory
dot("digraph {A -> B; B -> C; B -> D;}", file = "myfile.svg")

#export the example above in PostScript format
dot("digraph {A -> B; B -> C; B -> D;}", file = "myfile.ps")

#create a DOT graph and save the script in a string object in R
myString <- dot("digraph {A -> B;}", return = "verbatim")
```

Index

*Topic **diagram**

dot, [2](#)

*Topic **graphics**

dot, [2](#)

*Topic **literate**

dot, [2](#)

*Topic **plot**

dot, [2](#)

*Topic **visualization**

dot, [2](#)

dot, [2](#)