

Package ‘TLIC’

October 29, 2024

Type Package

Title The LIC for T Distribution Regression Analysis

Version 0.3

Date 2024-10-26

Description This comprehensive toolkit for T-distributed regression is designed as ``TLIC'' (The LIC for T Distribution Regression Analysis) analysis. It is predicated on the assumption that the error term adheres to a T-distribution. The philosophy of the package is described in Guo G. (2020) <[doi:10.1080/02664763.2022.2053949](https://doi.org/10.1080/02664763.2022.2053949)>.

License MIT + file LICENSE

Encoding UTF-8

RoxxygenNote 7.3.2

Imports stats, LaplacesDemon, fBasics

NeedsCompilation no

Author Guangbao Guo [aut, cre] (<<https://orcid.org/0000-0002-4115-6218>>),
Guofu Jing [aut]

Maintainer Guangbao Guo <ggb1111111@163.com>

Repository CRAN

Date/Publication 2024-10-29 05:10:06 UTC

Contents

terr	2
TLIC	2

Index	4
--------------	---

terr

terr function is used to generate a dataset where the error term follows a T-distribution

Description

This `terr` function generates a dataset with a specified number of observations and predictors, along with a response vector that has an error term following a T-distribution.

Usage

```
terr(n, nr, p, dist_type, ...)
```

Arguments

<code>n</code>	is the number of observations
<code>nr</code>	is the number of observations with a different error T distribution
<code>p</code>	is the dimension of the observation
<code>dist_type</code>	is the type where the error term obeys a T-distribution
<code>...</code>	is additional arguments for the T-distribution function

Value

`X, Y, e`

Examples

```
set.seed(12)
data <- terr(n = 1200, nr = 200, p = 5, dist_type = "student_t")
str(data)
```

TLIC

TLIC function based on LIC with T-distributed errors

Description

The `TLIC` function builds on the `LIC` function by introducing the assumption that the error term follows a T-distribution, thereby enhancing the length and information optimisation criterion.

Usage

```
TLIC(X, Y, alpha = 0.05, K = 10, nk = NULL, dist_type = "student_t")
```

Arguments

X	is a design matrix
Y	is a random response vector of observed values
alpha	is the significance level
K	is the number of subsets
nk	is the sample size of subsets
dist_type	is the type where the error term obeys a T-distribution

Value

MUopt, Bopt, MAEMUopt, MSEMUMopt, opt, Yopt

Examples

```
set.seed(12)
n <- 1200
nr <- 200
p <- 5
data <- terr(n, nr, p, dist_type = "student_t")
TLIC(data$X, data$Y, alpha = 0.05, K = 10, nk = n / 10, dist_type = "student_t")
```

Index

terr, 2

TLIC, 2