

Package ‘grobblR’

August 28, 2020

Title Creating Flexible, Reproducible 'PDF' Reports

Version 0.1.1

Description A tool which allows users the ability to intuitively create flexible, reproducible portable document format reports comprised of aesthetically pleasing tables, images, plots and/or text.

Depends R (>= 3.3.1)

Imports dplyr, ggplot2, glue, graphics, grDevices, grid, gridExtra, methods, magrittr, png, purrr, RCurl, stringr, tibble, tools

License MIT + file LICENSE

Language en-US

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

Suggests knitr, rmarkdown, R6, scales, testthat

VignetteBuilder knitr

NeedsCompilation no

Author Calvin Floyd [aut, cre, cph]

Maintainer Calvin Floyd <calvin.michael.floyd@gmail.com>

Repository CRAN

Date/Publication 2020-08-28 19:50:03 UTC

R topics documented:

add_aesthetic	2
add_column_headings	3
add_structure	4
aes_matrix	6
alter_at	6
column_names_to_row	8
convert_to_grob	9

convert_to_image_grob	9
convert_to_matrix_grob	10
ga_list	10
grob_col	14
grob_image	16
grob_layout	17
grob_matrix	18
grob_row	19
grob_text	21
grob_to_pdf	21
line_creator	23
view_grob	23

Index	25
--------------	-----------

add_aesthetic	<i>Add an Aesthetic</i>
---------------	-------------------------

Description

Add an aesthetic to a grob matrix object.

Usage

```
add_aesthetic(
  grob_object,
  aesthetic,
  value = NULL,
  group = c("cells", "column_names", "column_headings")
)
```

Arguments

grob_object	The R6 object outputted by either grob_matrix or grob_text .
aesthetic	The matrix aesthetic the user wishes to add.
value	A single value or a matrix of values the user wants to apply to the group of matrix / text elements for the given aesthetic. If a matrix of values is supplied, then the matrix must be of the same dimensions as the chosen subset of the matrix / text.
group	The group of the grob matrix object the user wants to add the aesthetic to. For objects initialized by grob_matrix , the user can add an aesthetic to the 'cells', the 'column_names' or the 'column_headings'. If the user is passing through an object initialized by grob_text , then only 'cells' will be accepted.

Details

Accepted aesthetics:

Matrix / Text

- background_alpha
- background_color
- border_color
- border_sides
- border_width
- font_face
- group_elements
- replace_na
- round_rect_radius
- text_align
- text_cex
- text_font
- text_color
- text_just
- text_v_align
- text_v_just
- text_rot

To see descriptions of the aesthetics above, see the documentation of [ga_list](#).

Value

The R6 object of the grob matrix class with its aesthetics properties altered.

Examples

```
df = data.frame(var1 = c(5, 14, 6, 10), var2 = c(3, 30, 17, 7))
df %>%
  grob_matrix() %>%
  add_aesthetic(aesthetic = 'text_color', value = 'red', group = 'cells') %>%
  view_grob()
```

add_column_headings *Add column headings to grob matrix*

Description

Add column headings onto an object initialized by [grob_matrix](#).

Usage

```
add_column_headings(mat, headings = list(), heading_cols = list())
```

Arguments

mat	The matrix the column headings will be added onto.
headings	The headings to be added onto the initial matrix, in a list with each heading a separate element. The list must have the same amount of elements as the heading_cols parameter.
heading_cols	Which column positions of the initial matrix the headings will be placed above, in a list with each heading's column positions a separate element. The list must have the same amount of elements as the headings parameter. Can either be numeric indices, or column names of the initial data.frame / matrix passed through <code>grob_matrix</code> . Default is an empty list. If unaltered, the function will assume the user wants to apply headings to all columns of the <code>grob_matrix</code> - in which case only one headings is allowed.

Details

The user must add column headings **before** adding or altering any structures or aesthetics.

Value

The initial matrix with column headings inserted into the first row.

Examples

```
data.frame(var1 = c(5, 14, 6, 10), var2 = c(3, 30, 17, 7)) %>%
  grob_matrix() %>%
  add_column_headings(c('HEADING')) %>%
  view_grob()
```

 add_structure

Add a Structure

Description

Add a structure to a grob matrix / image / text object.

Usage

```
add_structure(grob_object, structure, value)
```

Arguments

grob_object	The R6 object initialized by one of: <ul style="list-style-type: none"> • <code>grob_matrix</code> • <code>grob_image</code> • <code>grob_text</code>
structure	The structure the user wishes to add.
value	If <code>grob_object</code> is outputted by <code>grob_matrix</code> , then a single value, or a vector of values corresponding to each column of the initial object passed through <code>grob_matrix</code> , the user wants to apply to the grob matrix object. Otherwise, a single value to apply to the structure.

Details

Accepted structures:

- Matrix / Text**
- `column_widths_p`
 - `n_lines`
 - `padding_p`
 - `Image`
 - `aspect_ratio_multiplier`
 - `maintain_aspect_ratio`

To see descriptions of the structures above, see the documentation of [ga_list](#).

Value

The initial R6 object of the grob object class with its structure properties altered.

Examples

```
df = data.frame(x = c(5, 14, 6, 10), y = c(3, 30, 17, 7))
df %>%
  grob_matrix() %>%
  add_structure(structure = 'column_widths_p', value = c(1, 4)) %>%
  view_grob()

gg = ggplot2::ggplot(data = df, mapping = ggplot2::aes(x = x, y = y)) +
  ggplot2::geom_line(color = 'red')

gg %>%
  grob_image() %>%
  view_grob()
```

aes_matrix	<i>Create a matrix based off the dimensions of a data.frame/matrix and a single value to make up its cells. Designed to be used as an aesthetic matrix within <code>ga_list</code>.</i>
------------	---

Description

Create a matrix based off the dimensions of a data.frame/matrix and a single value to make up its cells. Designed to be used as an aesthetic matrix within `ga_list`.

Usage

```
aes_matrix(df, value, column_names = FALSE)
```

Arguments

df	A data.frame/matrix the resulting matrix will get its dimensions from.
value	The single value that will make up the cells of the resulting matrix.
column_names	A TRUE/FALSE value indicating if the resulting aesthetic matrix is intended to be used for the column names.

Value

A matrix based on the dimensions of df and value.

alter_at	<i>Alter aesthetics / structures at certain areas of a grob matrix</i>
----------	--

Description

Flexibly alter the aesthetic / structure of a grob matrix object at specific points of the data.frame/matrix.

Usage

```
alter_at(
  grob_object,
  .f = NULL,
  ...,
  columns = NULL,
  rows = NULL,
  data = NULL,
  structure = NULL,
  aesthetic = NULL,
  group = NULL
)
```

Arguments

grob_object	The R6 grob object class initialized by grob_matrix or grob_text .
.f	A quosure style lambda <code>~ fun(.)</code> , which the user wants to apply to the specific subset of cells.
...	Logical predicates defined in terms of the variables in the initial data.frame/matrix, or if the user provides a new data.frame to evaluate via <code>data</code> . Multiple conditions are combined with <code>&</code> . Only rows where the condition evaluates to TRUE are evaluated. If no logical predicates provided, then the entire columns will be altered.
columns	A character vector of column names, or numeric column indices, of the initial data.frame/matrix, or <code>data</code> if it is provided, the user wishes to alter.
rows	A numeric vector of row indices, of the initial data.frame/matrix, or <code>data</code> if it is provided, the user wishes to alter. Ignored if the user is altering a structure and not an aesthetic.
data	A separate data.frame/matrix of the same dimensions as the initial data.frame/matrix which the <code>.f</code> function and any filters will be applied to. Must match the dimensions of the subset of the initial data.frame/matrix the user is attempting to alter. Ignored if the user is altering a structure and not an aesthetic.
structure	Which structure the user wants to make alterations to. If left NULL and <code>aesthetic</code> is left NULL, the function will look for the most previous altered structure, either via add_structure , or a previous application of <code>alter_at</code> . View the documentation of add_structure for a list of accepted structures
aesthetic	Which aesthetic the user wants to make alterations to. If left NULL and <code>structure</code> is left NULL, the function will look for the most previous altered aesthetic, either via add_aesthetic , or a previous application of <code>alter_at</code> . View the documentation of add_aesthetic for a list of accepted aesthetics.
group	Which group of elements the user wants to make alterations to. If left NULL, the function will look for the most previous altered group, either via add_aesthetic , or a previous application of <code>alter_at</code> .

Value

The R6 grob matrix object class with its aesthetic / structure properties altered.

Examples

```
df = data.frame(var1 = c(5, 14, 6, 10), var2 = c(3, 30, 17, 7))
df %>%
  grob_matrix() %>%
  add_aesthetic(aesthetic = 'text_color', group = 'cells', value = 'red') %>%
  alter_at(
    .f = ~ 'blue',
    abs(var2 - var1) > 1
  ) %>%
```

```
view_grob()

test_function = function(x) ifelse(x > 15, 2, 1)

df %>%
  grob_matrix() %>%
  alter_at(
    .f = ~ test_function(.),
    aesthetic = 'font_face',
    group = 'cells'
  ) %>%
  view_grob()

df %>%
  grob_matrix() %>%
  add_structure("column_widths_p", 1) %>%
  alter_at(
    .f = ~ 2,
    columns = 1
  ) %>%
  view_grob()
```

column_names_to_row *Take a data.frame/matrix and insert its column names as the first row of the resulting matrix.*

Description

Take a data.frame/matrix and insert its column names as the first row of the resulting matrix.

Usage

```
column_names_to_row(df)
```

Arguments

df The data.frame/matrix.

Value

A matrix of the initial data.frame/matrix with its column names as the first row.

convert_to_grob	<i>Takes in an object, and converts it to a grob based on inputted aesthetics arguments.</i>
-----------------	--

Description

Takes in an object, and converts it to a grob based on inputted aesthetics arguments.

Usage

```
convert_to_grob(x, height, width, aes_list = ga_list())
```

Arguments

x	The object which needs to be converted to a grob. Must be either: A data.frame/matrix, the file name of a .png image, a character string, a vector, a ggplot object, or NA (for an empty grob).
height	The numeric height in mm of the desired grob.
width	The numeric width in mm of the desired grob.
aes_list	The list outputted by <code>ga_list</code> which contains elements to adjust aesthetics to the grob of x. Different type of grobs have different types of elements of this list which will affect its aesthetics. Possible elements for character strings, matrices and images can be found in ga_list .

Value

A grob of x with aesthetics based on the `aes_list` parameter.

convert_to_image_grob	<i>Converts a raw .png file to a grob, with flexible aesthetics.</i>
-----------------------	--

Description

Converts a raw .png file to a grob, with flexible aesthetics.

Usage

```
convert_to_image_grob(.image, aes_list, height = numeric(), width = numeric())
```

Arguments

.image	The local path to the raw .png file.
aes_list	The list outputted by ga_list which gives the image grob its aesthetics.
height	A numeric value designating the total height of the matrix grob in mm.
width	A numeric value designating the total width of the matrix grob in mm.

Value

A grob of the raw .png file.

`convert_to_matrix_grob`

Converts a data.frame/matrix to a grob, with flexible aesthetics.

Description

Converts a data.frame/matrix to a grob, with flexible aesthetics.

Usage

```
convert_to_matrix_grob(
  .df,
  aes_list = list(),
  height = numeric(),
  width = numeric()
)
```

Arguments

<code>.df</code>	The data.frame/matrix to be converted to a grob.
<code>aes_list</code>	The list outputted by <code>ga_list</code> which gives the data.frame/matrix grob its aesthetics.
<code>height</code>	A numeric value designating the total height of the matrix grob in mm.
<code>width</code>	A numeric value designating the total width of the matrix grob in mm.

Value

A grob of `.df`, with the corresponding aesthetics.

`ga_list`

Grob Aesthetic / Structure List

Description

Grob aesthetic list used to control aesthetics and structures within `grob_col`, `grob_row` and `grob_layout`.

Usage

```
ga_list(  
  aspect_ratio_multiplier = NULL,  
  background_color = NULL,  
  background_alpha = NULL,  
  border_color = NULL,  
  border_sides = NULL,  
  border_width = NULL,  
  font_face = NULL,  
  group_elements = NULL,  
  text_color = NULL,  
  text_align = NULL,  
  text_v_align = NULL,  
  text_just = NULL,  
  text_v_just = NULL,  
  text_cex = NULL,  
  text_font = NULL,  
  text_rot = NULL,  
  replace_na = NULL,  
  round_rect_radius = NULL,  
  column_widths_p = NULL,  
  padding_p = NULL,  
  maintain_aspect_ratio = NULL,  
  n_lines = NULL,  
  cell_font_face = NULL,  
  cell_group_elements = NULL,  
  cell_background_color = NULL,  
  cell_background_alpha = NULL,  
  cell_border_color = NULL,  
  cell_border_sides = NULL,  
  cell_border_width = NULL,  
  cell_text_color = NULL,  
  cell_text_align = NULL,  
  cell_text_v_align = NULL,  
  cell_text_just = NULL,  
  cell_text_v_just = NULL,  
  cell_text_cex = NULL,  
  cell_text_font = NULL,  
  cell_text_rot = NULL,  
  cell_replace_na = NULL,  
  cell_round_rect_radius = NULL,  
  cell_column_widths_p = NULL,  
  cell_padding_p = NULL,  
  colname_font_face = NULL,  
  colname_group_elements = NULL,  
  colname_background_color = NULL,  
  colname_background_alpha = NULL,  
  colname_border_color = NULL,  
)
```

```

colname_border_sides = NULL,
colname_border_width = NULL,
colname_text_color = NULL,
colname_text_align = NULL,
colname_text_v_align = NULL,
colname_text_just = NULL,
colname_text_v_just = NULL,
colname_text_cex = NULL,
colname_text_font = NULL,
colname_text_rot = NULL,
colname_replace_na = NULL,
colname_round_rect_radius = NULL,
colname_column_widths_p = NULL,
colname_padding_p = NULL
)

```

Arguments

aspect_ratio_multiplier A numeric value which controls how much to increase/decrease the aspect ratio of images.

background_color Controls the background color of the elements of the text / matrix.

background_alpha Controls the background alpha/opacity of the elements of the text / matrix.

border_color Controls the color of the selected borders.

border_sides Controls the borders of the elements of the matrix. The input is a string with the possible words "top", "bottom", "left", "right" separated by commas. For example, "top, left, right" will put borders on the top, left and right side of the grid cell, but not the bottom. Default is "", or no borders.

border_width Controls the line width density/thickness of the selected borders.

font_face Controls the font face of the elements of the matrix. Currently only numeric font face's are accepted. See [gpar](#) for more information.

group_elements A boolean argument on whether like, adjacent matrix elements should be grouped together into a single element.

text_color Controls the text color of the elements of the text / matrix.

text_align Controls where the text in each cell will be centered around, horizontally. A numeric value between 0 and 1, with 0 being all the way to the left of the cell, and 1 being all the way to the right of the cell. Default is 0.5. Can also input 'left', 'right' or 'center', which will also make edits to text_just to make the text completely left-justified, right-justified or centered, respectively.

text_v_align Controls where the text in each grid cell will be centered around, vertically. A numeric value between 0 and 1, with 0 being all the way to the bottom of the grid cell, and 1 being all the way to the top of the grid cell. Default is 0.5. Can also input 'top', 'bottom' or 'center', which will also make edits to text_v_just to make the text completely top-justified, bottom-justified or centered, respectively.

text_just	Controls the horizontal justification of the text in the matrix. A numeric value between 0 and 1, with 0 being left justification and 1 being right justification. Default is 0.5, or center justification. Can also input 'left', 'right' or 'center', which will also make edits to text_align to make the text completely left-justified, right-justified or centered, respectively.
text_v_just	Controls the vertical justification of the text in the matrix. A numeric value between 0 and 1, with 0 being bottom justification and 1 being top justification. Default is 0.5, or center justification. Can also input 'top', 'bottom' or 'center', which will also make edits to text_v_align to make the text completely top-justified, bottom-justified or centered, respectively.
text_cex	Controls the size of the text within the matrix. Default is automatic text sizing based on the length of the elements within the matrix, the row heights and the column widths.
text_font	Controls the font family within the text / matrix. Default is 'sans'.
text_rot	Controls the rotation in degrees of the text within the matrix. Default is 0 degrees Please be aware that the automatic text sizing will not react properly if the text is angled at anything other than 0 degrees.
replace_na	Controls what NA values in matrix will be replaced with. Default is an empty string.
round_rect_radius	Controls the radius of the corners of the rectangles matrix text is laid on top of.
column_widths_p	If automatic column widths are not desired, the user can provide a vector of width proportions corresponding to each column of the matrix.
padding_p	Controls the amount of proportional padding around each matrix cell.
maintain_aspect_ratio	A boolean argument which indicates whether the aspect ratio of the image should be maintained. Default is FALSE - meaning the image will be stretched to fit the designated grid area.
n_lines	The maximum number of lines is desired for the character string to be broken up into.
cell_background_alpha, cell_background_color, cell_border_color, cell_border_sides, cell_border_width	These arguments correspond to that aesthetic / structure for cells of a matrix. All are overridden by the corresponding arguments without cell_ in front of them.
colname_background_alpha, colname_background_color, colname_border_color, colname_border_sides, colname_border_width	These arguments correspond to that aesthetic / structure for column names of a matrix. All are overridden by the corresponding arguments without colname_ in front of them.

Details

Most of the matrix aesthetics / structures are inputted into [gpar](#). More in-depth details on input possibilities can be found in its documentation.²

To see which of the arguments are aesthetics and what types of grobs they apply to, view the documentation of [add_aesthetic](#).

To see which of the arguments are structures and what types of grobs they apply to, view the documentation of [add_structure](#).

For the color aesthetics (most notably `background_color`), inputting "none" will remove the color entirely, so the color will appear transparent.

Value

A list with all possible aesthetic / structure elements.

grob_col	<i>Grob Column</i>
----------	--------------------

Description

The grob-column function where an object is converted a grob. Works within [grob_row](#).

Usage

```
grob_col(
  ...,
  p = 1,
  width = NA_real_,
  aes_list = ga_list(),
  border = FALSE,
  border_aes_list = ga_list(),
  title = "",
  title_aes_list = ga_list(),
  title_p = 0.15,
  title_height = NA_real_,
  caption = "",
  caption_aes_list = ga_list(),
  caption_p = 0.15,
  caption_height = NA_real_,
  padding_p = 0.05,
  padding = NA_real_,
  hjust = 0.5,
  vjust = 0.5
)
```

Arguments

...	Either the object to be converted to a grob, or a combination of grob-rows which need to be converted to sub-grobs.
p	The numeric proportion of the width given to the outer grob-row which should be given to the grob-column outputted by this function. Defaults to 1.

width	The numeric width of the grob-column in millimeters. Overrides the p parameter.
aes_list	The list outputted by <code>ga_list</code> , which controls aesthetics object within the grob-column.
border	A TRUE/FALSE argument corresponding to whether or not a border around the outputted grob-column is desired. Defaults to FALSE.
border_aes_list	The list outputted by <code>ga_list</code> , which controls aesthetics of the borders. Only two aesthetics that can be tweaked for borders are <code>border_color</code> , <code>border_width</code> and <code>border_sides</code> . Ignored if border is set to FALSE.
title	A character string which will be displayed as the title of the grob-column.
title_aes_list	The list outputted by <code>ga_list</code> , which controls aesthetics of the title of the grob-column.
title_p	The numeric proportion of height within the grob-column which will be used by the title grob.
title_height	The numeric height in mm within the grob-column which will be used by the title grob. Will override <code>title_p</code> if provided.
caption	A character string which will be displayed as the caption of the grob-column.
caption_aes_list	The list outputted by <code>ga_list</code> , which controls aesthetics of the caption of the grob-column.
caption_p	The numeric proportion of height within the grob-column which will be used by the caption grob.
caption_height	The numeric height in mm within the grob-column which will be used by the caption grob. Will override <code>caption_p</code> if provided.
padding_p	The proportion of the minimum of the height and width which will be used for the padding around the edge of the grob-column. Overridden by any numeric value provided in the padding parameter.
padding	The numeric amount of padding around the edge of the grob-column in millimeters. Overrides the <code>padding_p</code> parameter.
hjust	A numeric value which will determine the alignment of the grob horizontally within its designated area. A value of 0 means moving the grob all the way to the left, a value of 1 means moving the grob all the way to the right and a value of 0.5 means keeping the grob in the middle. Defaults to 0.5. The grob-column is moved around within its padding, so if there is no padding, then <code>hjust</code> will be rendered useless.
vjust	A numeric value which will determine the alignment of the grob vertically within its designated area. A value of 0 means moving the grob all the way to the bottom, a value of 1 means moving the grob all the way to the top and a value of 0.5 means keeping the grob in the middle. Defaults to 0.5. The grob-column is moved around within its padding, so if there is no padding, then <code>vjust</code> will be rendered useless.

Value

An R6 class object containing all the information needed to create the grob-column.

Examples

```
grob_col(  
  "grob-column",  
  aes_list = ga_list(  
    text_color = "red",  
    background_color = "gray90"  
  )  
) %>%  
view_grob(100, 100)
```

grob_image

Grob Image

Description

Initialize a grob image object, to be used within `grob_col`.

Usage

```
grob_image(x)
```

Arguments

`x` Either a ggplot object, a file path to .png image or a URL to a .png image.

Value

An R6 object of the grob image class.

Examples

```
gg = data.frame(x = c(5, 14, 6, 10), y = c(3, 30, 17, 7)) %>%  
  ggplot2::ggplot(mapping = ggplot2::aes(x = x, y = y)) +  
  ggplot2::geom_line(color = 'red')  
  
gg %>%  
  grob_image() %>%  
  view_grob()
```


grob_layout

*Grob Layout***Description**

The main grob1R function which contains and organizes `grob_col`'s and `grob_row`'s, giving the overall grob-layout its shape.

Usage

```
grob_layout(
  ...,
  height = 280,
  width = 216,
  title = "",
  title_aes_list = ga_list(),
  title_p = 0.1,
  title_height = NA_real_,
  caption = "",
  caption_aes_list = ga_list(),
  caption_p = 0.05,
  caption_height = NA_real_,
  padding_p = 0.05,
  padding = NA_real_,
  page_number = ""
)
```

Arguments

<code>...</code>	The combination of <code>grob-rows</code> and <code>grob-columns</code> which will help give the main grob-layout outputted its structure and aesthetics.
<code>height</code>	The numeric height of the grob-layout in millimeters. Default is 280 mm - which is the height of an upright 8.5 x 11 inches piece of copy paper.
<code>width</code>	The numeric width of the grob in millimeters. Default is 216 mm - which is the width of an upright 8.5 x 11 inches piece of copy paper.
<code>title</code>	A character string which will be displayed as the title of the grob-layout.
<code>title_aes_list</code>	The list outputted by <code>ga_list</code> , which controls aesthetics of the title of the grob-layout.
<code>title_p</code>	The numeric proportion the grob-layout's height will be used by the title grob.
<code>title_height</code>	The numeric height in mm within the grob-layout which will be used by the title grob. Will override <code>title_p</code> if provided.
<code>caption</code>	A character string which will be displayed as the caption at the bottom of the grob-layout.

caption_aes_list	The list outputted by <code>ga_list</code> , which controls aesthetics of the caption of the grob-layout.
caption_p	The numeric proportion of height within the grob-layout and its allotted space which will be used by the caption grob.
caption_height	The numeric height in mm within the grob-layout which will be used by the caption grob. Will override <code>caption_p</code> if provided.
padding_p	The proportion of the minimum of the height and width which will be used for the padding around the edge of the grob-layout. Overridden by any numeric value provided in the <code>padding</code> parameter.
padding	The numeric amount of padding around the edge of the grob-layout in millimeters.
page_number	A single value that can be converted to an integer for the page number in the bottom right of the grob-layout within its padding. If it cannot be converted to an integer, the page number will not appear.

Details

Learn more in `vignette("grob_layout")`

Value

An R6 class object containing all information necessary to create the overall grob-layout.

Examples

```
grob_layout(
  grob_row(grob_col(1, border = TRUE), grob_col(2, border = TRUE)),
  grob_row(grob_col(3, border = TRUE))
) %>%
  view_grob(100, 100)
```

`grob_matrix`

Grob Matrix

Description

Initialize a grob matrix object, to be used within `grob_col`.

Usage

```
grob_matrix(x)
```

Arguments

`x` Either a `data.frame`, a matrix or a vector.

Details

Learn more in vignette("grob_matrix")

Value

An R6 object of the grob matrix class.

Examples

```
data.frame(  
  v1 = c(15, 4, 16, 11),  
  v2 = c(10, 30, 3, 10)  
) %>%  
  grob_matrix() %>%  
  view_grob()
```

grob_row

Grob Row

Description

The grob-row function which helps gives the grob from the [grob_layout](#) function its shape. Encompasses [grob_col](#) within the overall grob-layout.

Usage

```
grob_row(  
  ...,  
  p = 1,  
  height = NA_real_,  
  border = FALSE,  
  border_aes_list = ga_list(),  
  title = "",  
  title_aes_list = ga_list(),  
  title_p = 0.15,  
  title_height = NA_real_,  
  caption = "",  
  caption_aes_list = ga_list(),  
  caption_p = 0.15,  
  caption_height = NA_real_,  
  padding_p = 0.05,  
  padding = NA_real_  
)
```

Arguments

...	A series of <code>grob_col</code> 's.
<code>p</code>	The numeric proportion of the given height which should be given to sub-grobs outputted in the grob-row. Defaults to 1. Overridden if a height is supplied.
<code>height</code>	The numeric height of the grob-row in millimeters. Overrides the <code>p</code> parameter.
<code>border</code>	A TRUE/FALSE argument corresponding to whether or not a border around the outputted grob-row is desired. Defaults to FALSE.
<code>border_aes_list</code>	The list outputted by <code>ga_list</code> , which controls aesthetics of the borders. Ignored if <code>border</code> is set to FALSE.
<code>title</code>	A character string which will be displayed as the title of the grob-row.
<code>title_aes_list</code>	The list outputted by <code>ga_list</code> , which controls aesthetics of the title of the grob-row.
<code>title_p</code>	The numeric proportion of height within the grob-row which will be used by the title grob.
<code>title_height</code>	The numeric height in mm within the <code>grob_column</code> which will be used by the title grob. Will override <code>title_p</code> if provided.
<code>caption</code>	A character string which will be displayed as the caption of the grob-row.
<code>caption_aes_list</code>	The list outputted by <code>ga_list</code> , which controls aesthetics of the caption of the grob-row.
<code>caption_p</code>	The numeric proportion of height within the grob-row which will be used by the caption grob.
<code>caption_height</code>	The numeric height in mm within the <code>grob_column</code> which will be used by the caption grob. Will override <code>caption_p</code> if provided.
<code>padding_p</code>	The proportion of the minimum of the height and width which will be used for the padding around the edge of the grob-row. Overridden by any numeric value provided in the <code>padding</code> parameter.
<code>padding</code>	The numeric amount of padding around the edge of the grob-row in millimeters. Overrides the <code>padding_p</code> parameter.

Value

An R6 class object which contains all the information needed to carry on to its grob-columns and create the grob-row.

Examples

```
grob_row(
  grob_col(1, border = TRUE),
```

```
grob_col(2, border = TRUE)
) %>%
view_grob(100, 100)
```

grob_text

Grob Text

Description

Initialize a grob text object, to be used within [grob_col](#).

Usage

```
grob_text(x)
```

Arguments

x A single character string.

Value

An R6 object of the grob matrix class.

Examples

```
"The quick brown fox jumps over the lazy dog" %>%
grob_text() %>%
view_grob()
```

grob_to_pdf

Grob Layout to PDF

Description

Converts a single grob-layout to a PDF, or combines multiple grob-layouts into a multiple page PDF document.

Usage

```
grob_to_pdf(
  ...,
  file_name = character(),
  add_page_numbers = FALSE,
  meta_data_title = character()
)
```

Arguments

...	The single <code>grob_layout</code> , or series of <code>grob_layout</code> 's which will be converted to a PDF document.
<code>file_name</code>	The desired file name of the resulting PDF document in character format.
<code>add_page_numbers</code>	If TRUE, page numbers will be added to the bottom right corners of the pages of the document, based on the order of the grob-layouts listed.
<code>meta_data_title</code>	Title string to embed as the /Title field in the file. If not provided, it will default to the <code>file_name</code> provided.

Details

In the case of multiple page documents, the dimensions of the overall document will be determined by the dimensions of the first grob-layout listed.

Value

A PDF document of the grob-layout(s) which will be saved to the working directory.

Examples

```
grob_layout(
  grob_row(
    grob_col(1, border = TRUE),
    grob_col(2, border = TRUE),
    border = TRUE
  ),
  grob_row(
    grob_col(3, border = TRUE),
    grob_col(
      grob_row(grob_col(4, border = TRUE), border = TRUE),
      grob_row(grob_col(5, border = TRUE), border = TRUE),
      border = TRUE
    ),
    border = TRUE
  )
) %>%
grob_to_pdf(
  file_name = file.path(tempdir(), "test.pdf"),
  meta_data_title = "Test PDF"
)
```

line_creator	<i>Breaks down character strings into one or several lines, and determines if it would fit into a specific height and width.</i>
--------------	--

Description

Breaks down character strings into one or several lines, and determines if it would fit into a specific height and width.

Usage

```
line_creator(
  cex_val,
  string,
  height = numeric(),
  width = numeric(),
  units = c("mm"),
  sep = "\n"
)
```

Arguments

cex_val	The text cex multiplier applied to the string.
string	The character string needed to be broken down into several lines.
height	A numeric value designating the total height of the matrix grob in mm.
width	A numeric value designating the total width of the matrix grob in mm.
units	millimeters
sep	The separator within the character string which designates where a new line should start.

Value

A list containing a vector with each index equal to a line of the broken-down string, a TRUE/FALSE value indicating whether the lines will fit within equal sized rows and the widths in mm of each of the lines.

view_grob	<i>View Grob</i>
-----------	------------------

Description

View an grob outputted by one of the grob_ functions with a given width and height.

Usage

```
view_grob(grob, height = NA_real_, width = NA_real_)
```

Arguments

<code>grob</code>	An object outputted by one of the following functions: <ul style="list-style-type: none">• <code>grob_matrix</code>• <code>grob_image</code>• <code>grob_row</code>• <code>grob_col</code>• <code>grob_layout</code>
<code>height</code>	The numeric height in millimeters the user wishes to view the grob in.
<code>width</code>	The numeric width in millimeters the user wishes to view the grob in.

Details

Plotted with `gridExtra::grid.arrange()`.

Examples

```
df = data.frame(
  x = c(15, 4, 16, 11),
  y = c(10, 30, 3, 10)
)

df %>%
  grob_matrix() %>%
  view_grob()

gg = ggplot2::ggplot(data = df, mapping = ggplot2::aes(x = x, y = y)) +
  ggplot2::geom_line(color = 'red')

gg %>%
  grob_image() %>%
  view_grob()
```


Index

`add_aesthetic`, [2](#), [7](#), [14](#)
`add_column_headings`, [3](#)
`add_structure`, [4](#), [7](#), [14](#)
`aes_matrix`, [6](#)
`alter_at`, [6](#)

`column_names_to_row`, [8](#)
`convert_to_grob`, [9](#)
`convert_to_image_grob`, [9](#)
`convert_to_matrix_grob`, [10](#)

`ga_list`, [3](#), [5](#), [6](#), [9](#), [10](#), [10](#), [15](#), [17](#), [18](#), [20](#)
`gpar`, [12](#), [13](#)
`gridExtra::grid.arrange()`, [24](#)
`grob_col`, [10](#), [14](#), [16–21](#), [24](#)
`grob_image`, [5](#), [16](#), [24](#)
`grob_layout`, [10](#), [17](#), [19](#), [22](#), [24](#)
`grob_matrix`, [2–5](#), [7](#), [18](#), [24](#)
`grob_row`, [10](#), [14](#), [17](#), [19](#), [24](#)
`grob_text`, [2](#), [5](#), [7](#), [21](#)
`grob_to_pdf`, [21](#)

`line_creator`, [23](#)

`view_grob`, [23](#)