

# Package ‘rockx’

February 12, 2025

**Title** Easily Import Data from Your 'ODK-X Sync Endpoint'

**Version** 0.0.2

**Description** Provides helper functions for authenticating and retrieving data from your 'ODK-X Sync Endpoint'. This is an early release intended for testing and feedback.

**License** MIT + file LICENSE

**Depends** R (>= 4.1.0)

**Encoding** UTF-8

**RoxygenNote** 7.3.2

**Suggests** knitr, rmarkdown, testthat (>= 3.0.0)

**Config/testthat/edition** 3

**VignetteBuilder** knitr

**Imports** dplyr, httr, jsonlite, purrr, tidyr, rlang

**NeedsCompilation** no

**Author** Emil Rossing [aut, cre]

**Maintainer** Emil Rossing <hello@sapiens-solutions.com>

**Repository** CRAN

**Date/Publication** 2025-02-12 20:10:01 UTC

## Contents

download_attachments . . . . .	2
get_all_rows . . . . .	2
get_credentials . . . . .	3
get_tables . . . . .	3
get_table_metadata . . . . .	4
set_username_and_password . . . . .	4

<b>Index</b>	<b>5</b>
--------------	----------

---

download\_attachments    *Download attachments for table rows*

---

### Description

This function downloads attachments for the specified table rows and saves them in a structured directory. Each row with attachments will have a dedicated folder under the table-specific subdirectory.

### Usage

```
download_attachments(  
  rows,  
  table_meta,  
  save_to_directory,  
  skip_if_instance_folder_exists = FALSE  
)
```

### Arguments

**rows**                    A tibble or data frame containing the table rows to download attachments for.

**table\_meta**            List. Metadata for the table, as returned by `get_table_metadata(table_name)`.

**save\_to\_directory**    String. The parent directory where attachments will be saved. A subdirectory with the name of the table will be created, and each row with attachments will have its own subfolder under this directory.

**skip\_if\_instance\_folder\_exists**    Logical. If TRUE, rows with an existing instance folder will be skipped to avoid re-downloading attachments. Defaults to FALSE.

### Value

Invisibly returns NULL. Downloads the attachments as a side effect.

---

get\_all\_rows            *Retrieve all rows from a table*

---

### Description

This function retrieves all rows for a given table from the ODK-X Sync Endpoint and tries to parse known types based on the table's schema definition.

### Usage

```
get_all_rows(table_name)
```

**Arguments**

table\_name      String. The name of the table from which to retrieve rows.

**Value**

A tibble containing all rows.

---

get\_credentials      *Retrieve API Credentials*

---

**Description**

This function fetches the stored API credentials from environment variables.

**Usage**

```
get_credentials()
```

**Value**

A list containing username, password, and server\_url.

---

get\_tables      *Retrieve Tables from ODK-X Sync Endpoint*

---

**Description**

This function retrieves the list of tables from the ODK-X Sync Endpoint by making a paginated GET request to (<server\_url>)/odktables/default/tables. It uses BASIC authentication with the credentials stored via rockx::set\_username\_and\_password().

**Usage**

```
get_tables()
```

**Value**

A tibble containing the list of found tables.

get\_table\_metadata      *Retrieve table metadata from ODK-X Sync Endpoint*

---

**Description**

This function retrieves the table metadata for a given table from the ODK-X Sync Endpoint.

**Usage**

```
get_table_metadata(table_name)
```

**Arguments**

table\_name      String. The name of the table.

**Value**

A list containing table metadata.

---

set\_username\_and\_password  
*Set Username, Password, and Server URL for API Authentication*

---

**Description**

This function sets the environment variables ROCKX\_USERNAME, ROCKX\_PASSWORD, and ROCKX\_SERVER\_URL for authentication and specifying the ODK-X Sync Endpoint.

**Usage**

```
set_username_and_password(username, password, server_url)
```

**Arguments**

username      A character string containing the API username.  
password      A character string containing the API password.  
server\_url    A character string containing the URL of the ODK-X sync endpoint (e.g., "https://my.sync-endpoint.com").

**Value**

A message confirming that credentials and server URL have been set.

**Examples**

```
rockx::set_username_and_password("my_user", "my_password", "https://my.sync-endpoint.com")
```

# Index

`download_attachments`, [2](#)

`get_all_rows`, [2](#)

`get_credentials`, [3](#)

`get_table_metadata`, [4](#)

`get_tables`, [3](#)

`set_username_and_password`, [4](#)