

Package ‘surveydown’

November 27, 2024

Title Markdown-Based Surveys Using 'Quarto' and 'shiny'

Version 0.5.1

Description Generate surveys using markdown and R code chunks. Surveys are composed of two files: a survey.qmd 'Quarto' file defining the survey content (pages, questions, etc), and an app.R file defining a 'shiny' app with global settings (libraries, database configuration, etc.) and server configuration options (e.g., conditional skipping / display, etc.). Survey data collected from respondents is stored in a 'PostgreSQL' database. Features include controls for conditional skip logic (skip to a page based on an answer to a question), conditional display logic (display a question based on an answer to a question), a customizable progress bar, and a wide variety of question types, including multiple choice (single choice and multiple choices), select, text, numeric, multiple choice buttons, text area, and dates. Because the surveys render into a 'shiny' app, designers can also leverage the reactive capabilities of 'shiny' to create dynamic and interactive surveys.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.2

VignetteBuilder knitr

Depends R (>= 4.0.0)

Suggests knitr, testthat, glue

Imports DBI, DT, fs, htmltools, markdown, pool, quarto, RPostgres, rstudioapi, rvest, shiny, shinyjs, shinyWidgets, usethis, utils, xml2, yaml

URL <https://pkg.surveydown.org>

BugReports <https://github.com/surveydown-dev/surveydown/issues>

NeedsCompilation no

Author John Paul Helveston [aut, cre, cph]

(<<https://orcid.org/0000-0002-2657-9191>>),

Pingfan Hu [aut, cph] (<<https://orcid.org/0009-0001-4877-4844>>),

Bogdan Bunea [aut, cph] (<<https://orcid.org/0009-0006-2942-0588>>),

Stefan Munnes [ctb]

Maintainer John Paul Helveston <john.helveston@gmail.com>

Repository CRAN

Date/Publication 2024-11-27 13:20:02 UTC

Contents

sd_add_page	2
sd_add_question	3
sd_close	5
sd_completion_code	6
sd_copy_value	7
sd_create_survey	8
sd_create_translations	9
sd_database	10
sd_display_question	11
sd_display_value	12
sd_get_data	12
sd_get_url_pars	13
sd_include_folder	14
sd_is_answered	15
sd_next	16
sd_output	18
sd_question	19
sd_redirect	22
sd_server	23
sd_setup	26
sd_set_password	27
sd_show_if	28
sd_show_password	29
sd_skip_if	30
sd_store_value	31
sd_ui	32
sd_version	33

Index **35**

sd_add_page

Add a Page Template to the Current Document

Description

This function inserts a template for a surveydown page at the current cursor position in the active RStudio document. It provides a basic structure for a new page, including a title, content area, and a next button. If the function call exists in the document, it will be removed before inserting the template.

Usage

```
sd_add_page()
```

Details

IMPORTANT: This function should be run outside any division or R code chunk in your 'Quarto' document. Running it inside a division or code chunk may result in an incorrect page structure.

The function performs the following steps:

1. Checks for and removes any existing `sd_add_page()` function call in the document.
2. Inserts a template at the current cursor position.

The template includes:

- A div with class 'sd-page' and a placeholder page ID
- A placeholder for the page title
- A placeholder for page contents
- An R code chunk with a placeholder for questions and a next button

Value

This function does not return a value. It modifies the active document as a side effect by inserting text and potentially removing a function call.

Examples

```
if (interactive()) {  
  library(surveydown)  
  
  # Insert a new page template  
  sd_add_page()  
}
```

sd_add_question

Add a Question Template to the Current Document

Description

This function inserts a template for a surveydown question at the current cursor position in the active RStudio document. It supports various question types and automatically removes the function call before inserting the template if it exists in the document.

Usage

```
sd_add_question(type = "mc", chunk = FALSE)
```

Arguments

type	<p>A character string specifying the type of question template to insert. Default is "mc" (multiple choice). Available options are:</p> <ul style="list-style-type: none">• "mc": Multiple choice (single selection)• "select": Dropdown selection• "mc_multiple": Multiple choice (multiple selections)• "mc_buttons": Multiple choice with button layout (single selection)• "mc_multiple_buttons": Multiple choice with button layout (multiple selections)• "text": Short text input• "textarea": Long text input• "numeric": Numeric input• "slider": Slider input• "date": Date input• "daterange": Date range input
chunk	<p>Logical. If TRUE, the code will be generated with the R code chunk wrapper. Defaults to FALSE.</p>

Details

The function performs the following steps:

1. Checks for and removes any existing `sd_add_question()` function call in the document.
2. Inserts the appropriate question template at the current cursor position.

Value

This function does not return a value. It modifies the active document as a side effect by inserting text and potentially removing a function call.

Examples

```
if (interactive()) {  
  library(surveydown)  
  
  # Insert a default multiple choice question template  
  sd_add_question()  
  
  # Insert a text input question template  
  sd_add_question("text")  
  
  # Insert a slider question template  
  sd_add_question("slider")  
}
```

`sd_close`*Create a 'Close' Button to Exit the Survey*

Description

This function creates a 'Close' button that, when clicked, will trigger the exit process for the survey. Depending on the server-side configuration, this may show a rating question or a simple confirmation dialog before attempting to close the current browser tab or window.

Usage

```
sd_close(label = NULL)
```

Arguments

<code>label</code>	Character string. The label of the 'Close' button. Defaults to NULL, in which case the word "Exit Survey" will be used.
--------------------	---

Details

The function generates a 'shiny' action button that, when clicked, triggers the 'show_exit_modal' event. The server-side logic (controlled by the `rate_survey` parameter in `sd_server()`) determines whether to show a rating question or a simple confirmation dialog.

The function also includes a custom message handler for closing the window. This is necessary because some browsers may not allow JavaScript to close windows that were not opened by JavaScript. In such cases, the user will be prompted to close the tab manually.

Value

A 'shiny' tagList containing the 'Close' button UI element and associated JavaScript for the exit process.

Note

The actual behavior of the exit process (whether to show a rating question or not) is controlled by the `rate_survey` parameter in the `sd_server()` function, not in this UI function.

See Also

[sd_server](#)

Examples

```
if (interactive()) {  
  library(surveydown)  
  
  # Get path to example survey file  
  survey_path <- system.file("examples", "sd_close.qmd",
```

```
      package = "surveydown")

# Copy to a temporary directory
temp_dir <- tempdir()
file.copy(survey_path, file.path(temp_dir, "survey.qmd"))
orig_dir <- getwd()
setwd(temp_dir)

# Define a minimal server
server <- function(input, output, session) {
  sd_server()
}

# Run the app
shiny::shinyApp(ui = sd_ui(), server = server)

# Clean up
setwd(orig_dir)
}
```

sd_completion_code *Generate a Random Completion Code*

Description

This function generates a random completion code with a specified number of digits. The code is returned as a character string.

Usage

```
sd_completion_code(digits = 6)
```

Arguments

digits An integer specifying the number of digits in the completion code. Must be a positive integer. Default is 6.

Value

A character string representing the random completion code.

Examples

```
library(surveydown)

sd_completion_code() # generates a 6-digit code
sd_completion_code(digits = 8) # generates an 8-digit code
sd_completion_code(digits = 4) # generates a 4-digit code
sd_completion_code(digits = 10) # generates a 10-digit code
```

sd_copy_value	<i>Create a copy of a value</i>
---------------	---------------------------------

Description

This function creates a copy of an input value and makes it available as a new output. The new output can then be displayed using `sd_output()`.

Usage

```
sd_copy_value(id, id_copy)
```

Arguments

<code>id</code>	Character string. The ID of the input value to copy.
<code>id_copy</code>	Character string. The ID for the new copy (must be different from <code>id</code>).

Value

NULL invisibly. This function is called for its side effects.

See Also

`sd_output()` for displaying the copied value

Examples

```
if (interactive()) {
  library(surveydown)

  # Get path to example survey file
  survey_path <- system.file("examples", "sd_ui.qmd",
                             package = "surveydown")

  # Copy to a temporary directory
  temp_dir <- tempdir()
  file.copy(survey_path, file.path(temp_dir, "sd_copy_value.qmd"))
  orig_dir <- getwd()
  setwd(temp_dir)

  # Define a minimal server
  server <- function(input, output, session) {

    # Make a copy of the "name" variable to call its value a second time
    sd_copy_value(id = "name", id_copy = "name_copy")

    sd_server()
  }
}
```

```
# Run the app
shiny::shinyApp(ui = sd_ui(), server = server)

# Clean up
setwd(orig_dir)
}
```

sd_create_survey *Create a new survey template*

Description

This function creates a new survey template by copying files from the package's template directory to a specified path. It handles file conflicts and provides appropriate warnings and feedback.

Usage

```
sd_create_survey(path = getwd(), structure = "single")
```

Arguments

path	A character string specifying the directory where the survey template should be created. Defaults to the current working directory.
structure	A character string specifying the template structure to use. Must be either "single" or "multi". Defaults to "single".

Details

The function performs the following steps:

- If the specified path is the current working directory, it asks for user confirmation.
- Validates the specified structure ("single" or "multi").
- Creates the target directory if it doesn't exist.
- Copies all files from the package's template directory (based on the specified structure) to the target path.
- Preserves the directory structure of the template.
- Skips existing files and provides warnings for each skipped file.
- Handles .Rproj files specially, skipping if any .Rproj file already exists in the target directory.
- Provides feedback on whether files were copied or if all files already existed.

Value

Invisible NULL. The function is called for its side effects of creating files and providing user feedback.

Examples

```
if (interactive()) {  
  # Create a single-page survey template  
  sd_create_survey(structure = "single")  
  
  # Create a multi-page survey template  
  sd_create_survey(structure = "multi")  
}
```

sd_create_translations

Create a translations template file

Description

This function creates a template translations.yml file in the project root directory that users can customize to modify system messages.

Usage

```
sd_create_translations(language = "en", path = getwd())
```

Arguments

language	Character string specifying the language to use. See https://shiny.posit.co/r/reference/shiny/1.7.0/dateinput for supported languages. Also, if "en", "de", "es", "fr", or "it" is chosen, default messages in those languages will be used, otherwise the default English messages will be used. Defaults to "en".
path	Character string specifying the directory where the translations.yml file should be created. Defaults to the current working directory. The file should be placed in the root project folder of your surveydown survey.

Value

Invisible NULL.

Examples

```
if (interactive()) {  
  # Create English template  
  sd_create_translations()  
  
  # Create German template  
  sd_create_translations(language = "de")  
  
  # Create Japanese template  
  # Will use English messages but Japanese date picker - user can modify  
  # the messages as desired
```

```
sd_create_translations(language = "ja")
}
```

sd_database

Connect to a 'PostgreSQL' Database with Automatic Cleanup

Description

This function establishes a connection pool to a 'PostgreSQL' database (e.g. Supabase) and sets up automatic cleanup when the 'shiny' session ends.

Usage

```
sd_database(
  host = NULL,
  dbname = NULL,
  port = NULL,
  user = NULL,
  table = NULL,
  password = Sys.getenv("SURVEYDOWN_PASSWORD"),
  gssencmode = "prefer",
  ignore = FALSE,
  min_size = 1,
  max_size = Inf
)
```

Arguments

host	Character string. The host address of the Supabase database.
dbname	Character string. The name of the Supabase database.
port	Integer. The port number for the Supabase database connection.
user	Character string. The username for the Supabase database connection.
table	Character string. The name of the table to interact with in the Supabase database.
password	Character string. The password for the Supabase database connection. NOTE: While you can provide a hard-coded password here, we do NOT recommend doing so for security purposes. Instead, you should establish a password with <code>surveydown::sd_set_password()</code> , which will create a local <code>.Renviro</code> file that stores your password as a <code>SURVEYDOWN_PASSWORD</code> environment variable. The password argument uses this as the default value, so if you set a password properly with <code>surveydown::sd_set_password()</code> , then you can safely ignore using the password argument here.
gssencmode	Character string. The GSS encryption mode for the database connection. Defaults to "prefer". NOTE: If you have verified all connection details are correct but still cannot access the database, consider setting this to "disable". This can be necessary if you're on a secure connection, such as a VPN.

ignore	Logical. If TRUE, data will be saved to a local CSV file instead of the database. Defaults to FALSE.
min_size	Integer. The minimum number of connections in the pool. Defaults to 1.
max_size	Integer. The maximum number of connections in the pool. Defaults to Inf.

Value

A list containing the database connection pool (db) and the table name (table), or NULL if in ignore mode or if there's an error.

Examples

```
if (interactive()) {
  # Assuming SURVEYDOWN_PASSWORD is set in .Renvirom
  db <- sd_database(
    host = "aws-0-us-west-1.pooler.supabase.com",
    dbname = "postgres",
    port = "6--",
    user = "postgres.k-----i",
    table = "your-table-name",
    ignore = FALSE
  )

  # Print the structure of the connection
  str(db)

  # Close the connection pool when done
  if (!is.null(db)) {
    pool::poolClose(db$db)
  }
}
```

sd_display_question *Create a placeholder for a reactive survey question*

Description

This function is deprecated - use sd_output() instead.

Usage

```
sd_display_question(id)
```

Arguments

id A unique identifier for the question.

Value

A 'shiny' UI element that serves as a placeholder for the reactive question.

sd_display_value	<i>Display the value of a survey question</i>
------------------	---

Description

This function is deprecated - use `sd_output()` instead.

Usage

```
sd_display_value(id, display_type = "inline", wrapper = NULL, ...)
```

Arguments

<code>id</code>	The ID of the question to display
<code>display_type</code>	The type of display. Can be "inline" (default), "text", "verbatim", or "ui".
<code>wrapper</code>	A function to wrap the output
<code>...</code>	Additional arguments passed to the wrapper function

Value

A 'shiny' UI element displaying the question's value

sd_get_data	<i>Fetch data from a database table with automatic reactivity detection</i>
-------------	---

Description

This function retrieves all data from a specified table in a database. It automatically detects whether it's being used in a reactive context (e.g., within a 'shiny' application) and behaves accordingly. In a reactive context, it returns a reactive expression that automatically refreshes the data at specified intervals.

Usage

```
sd_get_data(db, refresh_interval = NULL)
```

Arguments

<code>db</code>	A list containing database connection details created using <code>sd_database()</code> . Must have elements: <ul style="list-style-type: none"> <code>db</code>: A DBI database connection object <code>table</code>: A string specifying the name of the table to query
<code>refresh_interval</code>	Numeric. The time interval (in seconds) between data refreshes when in a reactive context. Default is NULL, meaning the data will not refresh.

Value

In a non-reactive context, returns a data frame containing all rows and columns from the specified table. In a reactive context, returns a reactive expression that, when called, returns the most recent data from the specified database table.

Examples

```
# Non-reactive context example
## Not run:
library(surveydown)

# Assuming you have a database connection called db created using
# sd_database(), you can fetch data with:

data <- sd_get_data(db)
head(data)

# Reactive context example (inside a surveydown app)

server <- function(input, output, session) {
  data <- sd_get_data(db, refresh_interval = 10)

  output$data_table <- renderTable({
    data() # Note the parentheses to retrieve the reactive value
  })
}

## End(Not run)
```

sd_get_url_pars

Get URL Parameters in a 'shiny' Application

Description

This function retrieves URL parameters from the current 'shiny' session. It must be called from within a 'shiny' reactive context.

Usage

```
sd_get_url_pars(...)
```

Arguments

... Optional. Names of specific URL parameters to retrieve. If none are specified, all URL parameters are returned.

Value

A reactive expression that returns a list of URL parameters.

Examples

```

if (interactive()) {
  library(surveydown)

  # Get path to example survey file
  survey_path <- system.file("examples", "sd_redirect.qmd",
                             package = "surveydown")

  # Copy to a temporary directory
  temp_dir <- tempdir()
  file.copy(survey_path, file.path(temp_dir, "survey.qmd"))
  orig_dir <- getwd()
  setwd(temp_dir)

  # Define a minimal server
  server <- function(input, output, session) {

    # Reactive expression that generates a url with an id variable
    # parsed from the url
    url_redirect <- reactive({
      params <- sd_get_url_pars()
      id <- params["id"]
      return(paste0("https://www.google.com?id=", id))
    })

    # Create the redirect button
    sd_redirect(
      id = "redirect_url_pars",
      url = url_redirect(),
      button = TRUE,
      label = "Redirect"
    )

    sd_skip_if(
      input$screening_question == "end_1" ~ "end_page_1",
      input$screening_question == "end_1" ~ "end_page_2",
    )

    sd_server()
  }

  # Run the app
  shiny::shinyApp(ui = sd_ui(), server = server)

  # Clean up
  setwd(orig_dir)
}

```

Description

This function includes a specified folder to the 'shiny' resource path, making it accessible for serving static files in a 'shiny' application. It checks for pre-existing resource paths to avoid conflicts with folders already included by the package.

Usage

```
sd_include_folder(folder)
```

Arguments

folder A character string specifying the name of the folder to include. This folder should exist in the root directory of your 'shiny' app.

Value

NULL invisibly. The function is called for its side effect of adding a resource path to 'shiny'.

Examples

```
if (interactive()) {  
  library(shiny)  
  
  # Create an "images" folder  
  dir.create("images")  
  
  # Include the folder in the shiny resource path  
  sd_include_folder("images")  
}
```

sd_is_answered	<i>Check if a question is answered</i>
----------------	--

Description

This function checks if a given question has been answered by the user. For matrix questions, it checks if all sub-questions (rows) are answered.

Usage

```
sd_is_answered(question_id)
```

Arguments

question_id The ID of the question to check.

Value

A logical value: TRUE if the question is answered, FALSE otherwise.

Examples

```
if (interactive()) {
  library(surveydown)

  # Get path to example survey file
  survey_path <- system.file("examples", "sd_is_answered.qmd",
                             package = "surveydown")

  # Copy to a temporary directory
  temp_dir <- tempdir()
  file.copy(survey_path, file.path(temp_dir, "survey.qmd"))
  orig_dir <- getwd()
  setwd(temp_dir)

  # Define a minimal server
  server <- function(input, output, session) {

    sd_show_if(
      # If "apple_text" is answered, show the conditional question
      sd_is_answered("apple_text") ~ "other_fruit"
    )

    sd_server()
  }

  # Run the app
  shiny::shinyApp(ui = sd_ui(), server = server)

  # Clean up
  setwd(orig_dir)
}
```

sd_next

Create a 'Next' Button for Page Navigation

Description

This function creates a 'Next' button for navigating to the specified next page in a Surveydown survey. The button can be activated by clicking or by pressing the Enter key when visible.

Usage

```
sd_next(next_page = NULL, label = NULL)
```


Arguments

next_page	Character string. The ID of the next page to navigate to. This parameter is required.
label	Character string. The label of the 'Next' button. Defaults to NULL, in which case the word "Next" will be used.

Details

The function generates a 'shiny' action button that, when clicked or when the Enter key is pressed, sets the input value to the specified next page ID, facilitating page navigation within the Shiny application. The button is styled to appear centered on the page and includes a class for Enter key functionality.

Value

A 'shiny' tagList containing the 'Next' button UI element.

Examples

```
if (interactive()) {
  library(surveydown)

  # Get path to example survey file
  survey_path <- system.file("examples", "sd_next.qmd",
                             package = "surveydown")

  # Copy to a temporary directory
  temp_dir <- tempdir()
  file.copy(survey_path, file.path(temp_dir, "survey.qmd"))
  orig_dir <- getwd()
  setwd(temp_dir)

  # Define a minimal server
  server <- function(input, output, session) {
    sd_server()
  }

  # Run the app
  shiny::shinyApp(ui = sd_ui(), server = server)

  # Clean up
  setwd(orig_dir)
}
```

sd_output

*Output Function for Displaying reactive objects and values***Description**

Output Function for Displaying reactive objects and values

Usage

```
sd_output(
  id,
  type = NULL,
  width = "100%",
  display = "text",
  inline = TRUE,
  wrapper = NULL,
  ...
)
```

Arguments

id	Character string. A unique identifier for the output element.
type	Character string. Specifies the type of output. Can be "question", "value", or NULL. If NULL, the function behaves like shiny::uiOutput().
width	Character string. The width of the UI element. Defaults to "100%".
display	Character string. Specifies the display type for "value" outputs. Can be "text", "verbatim", or "ui". Only used when type = "value".
inline	Logical. Whether to render the output inline. Defaults to TRUE.
wrapper	Function. A function to wrap the output. Only used when type = "value".
...	Additional arguments passed to the underlying 'shiny' functions or the wrapper function.

Details

The function behaves differently based on the type parameter:

- If type is NULL, it acts like shiny::uiOutput().
- If type is "question", it creates a placeholder for a reactive survey question.
- If type is "value", it creates an output to display the value of a survey question, with the display style determined by the display parameter.

Value

A 'shiny' UI element, the type of which depends on the input parameters.

Examples

```
if (interactive()) {
  library(surveydown)

  # Get path to example survey file
  survey_path <- system.file("examples", "sd_output.qmd",
                             package = "surveydown")

  # Copy to a temporary directory
  temp_dir <- tempdir()
  file.copy(survey_path, file.path(temp_dir, "survey.qmd"))
  orig_dir <- getwd()
  setwd(temp_dir)

  # Define a minimal server
  server <- function(input, output, session) {
    sd_server()
  }

  # Run the app
  shiny::shinyApp(ui = sd_ui(), server = server)

  # Clean up
  setwd(orig_dir)
}
```

sd_question

Create a survey question

Description

This function creates various types of survey questions for use in a Surveydown survey.

Usage

```
sd_question(
  type,
  id,
  label,
  cols = "80",
  direction = "horizontal",
  status = "default",
  width = "100%",
  height = "100px",
  selected = NULL,
  label_select = "Choose an option...",
  grid = TRUE,
```

```

    individual = TRUE,
    justified = FALSE,
    force_edges = TRUE,
    option = NULL,
    placeholder = NULL,
    resize = NULL,
    row = NULL
)

```

Arguments

type	Specifies the type of question. Possible values are "select", "mc", "mc_multiple", "mc_buttons", "mc_multiple_buttons", "text", "textarea", "numeric", "slider", "date", "daterange", and "matrix".
id	A unique identifier for the question, which will be used as the variable name in the resulting survey data.
label	Character string. The label for the UI element, which can be formatted with markdown.
cols	Integer. Number of columns for the textarea input. Defaults to 80.
direction	Character string. The direction for button groups ("horizontal" or "vertical"). Defaults to "horizontal".
status	Character string. The status for button groups. Defaults to "default".
width	Character string. The width of the UI element. Defaults to "100%".
height	Character string. The height of the textarea input. Defaults to "100px".
selected	Value. The selected value(s) for certain input elements.
label_select	Character string. The label for the select input. Defaults to "Choose an option...".
grid	Logical. Whether to show a grid for slider input. Defaults to TRUE.
individual	Logical. Whether buttons in a group should be individually styled. Defaults to TRUE.
justified	Logical. Whether buttons in a group should fill the width of the parent div. Defaults to FALSE.
force_edges	Logical. Whether to force edges for slider input. Defaults to TRUE.
option	List. Options for the select, radio, checkbox, and slider inputs.
placeholder	Character string. Placeholder text for text and textarea inputs.
resize	Character string. Resize option for textarea input. Defaults to NULL.
row	List. Used for "matrix" type questions. Contains the row labels and their corresponding IDs.

Details

The function supports various question types:

- "select": A dropdown selection

- "mc": Multiple choice (single selection)
- "mc_multiple": Multiple choice (multiple selections allowed)
- "mc_buttons": Multiple choice with button-style options (single selection)
- "mc_multiple_buttons": Multiple choice with button-style options (multiple selections allowed)
- "text": Single-line text input
- "textarea": Multi-line text input
- "numeric": Numeric input
- "slider": Slider input
- "date": Date input
- "daterange": Date range input
- "matrix": Matrix-style question with rows and columns

For "matrix" type questions, use the row parameter to define the rows of the matrix. Each element in the row list should have a name (used as the row ID) and a value (used as the row label).

Value

A 'shiny' UI element wrapped in a div with a data attribute for question ID.

Examples

```
if (interactive()) {
  library(surveydown)

  # Get path to example survey file
  survey_path <- system.file("examples", "basic_survey.qmd",
                             package = "surveydown")

  # Copy to a temporary directory
  temp_dir <- tempdir()
  file.copy(survey_path, file.path(temp_dir, "survey.qmd"))
  orig_dir <- getwd()
  setwd(temp_dir)

  # Define a minimal server
  server <- function(input, output, session) {
    sd_server()
  }

  # Run the app
  shiny::shinyApp(ui = sd_ui(), server = server)

  # Clean up
  setwd(orig_dir)
}
```

`sd_redirect`*Create a Redirect Element for 'shiny' Applications*

Description

This function creates a UI element that redirects the user to a specified URL. It can be used in both reactive and non-reactive contexts within 'shiny' applications.

Usage

```
sd_redirect(  
  id,  
  url,  
  button = TRUE,  
  label = "Click here",  
  delay = NULL,  
  newtab = FALSE  
)
```

Arguments

<code>id</code>	A character string of a unique id to be used to identify the redirect button in the survey body.
<code>url</code>	A character string specifying the URL to redirect to.
<code>button</code>	A logical value indicating whether to create a button (TRUE) or a text element (FALSE) for the redirect. Default is TRUE.
<code>label</code>	A character string for the button or text label. Defaults to NULL, in which case the words "Click here" will be used.
<code>delay</code>	An optional numeric value specifying the delay in seconds before automatic redirection. If NULL (default), no automatic redirection occurs.
<code>newtab</code>	A logical value indicating whether to open the URL in a new tab (TRUE) or in the current tab (FALSE). Default is FALSE.

Value

In a reactive context, returns a function that when called, renders the redirect element. In a non-reactive context, returns the redirect element directly.

Examples

```
if (interactive()) {  
  library(surveydown)  
  
  # Get path to example survey file  
  survey_path <- system.file("examples", "sd_redirect.qmd",  
                             package = "surveydown")
```

```

# Copy to a temporary directory
temp_dir <- tempdir()
file.copy(survey_path, file.path(temp_dir, "survey.qmd"))
orig_dir <- getwd()
setwd(temp_dir)

# Define a minimal server
server <- function(input, output, session) {

  # Reactive expression that generates a url with an id variable
  # parsed from the url
  url_redirect <- reactive({
    params <- sd_get_url_pars()
    id <- params["id"]
    return(paste0("https://www.google.com?id=", id))
  })

  # Create the redirect button
  sd_redirect(
    id = "redirect_url_pars",
    url = url_redirect(),
    button = TRUE,
    label = "Redirect"
  )

  sd_skip_if(
    input$screening_question == "end_1" ~ "end_page_1",
    input$screening_question == "end_1" ~ "end_page_2",
  )

  sd_server()
}

# Run the app
shiny::shinyApp(ui = sd_ui(), server = server)

# Clean up
setwd(orig_dir)
}

```

sd_server

Server logic for a surveydown survey

Description

This function defines the server-side logic for a 'shiny' application used in surveydown. It handles various operations such as conditional display, progress tracking, page navigation, database updates for survey responses, and exit survey functionality.

Usage

```
sd_server(
  db = NULL,
  required_questions = NULL,
  all_questions_required = FALSE,
  start_page = NULL,
  admin_page = FALSE,
  auto_scroll = FALSE,
  rate_survey = FALSE,
  language = "en"
)
```

Arguments

db	A list containing database connection information created using <code>sd_database()</code> function. Defaults to <code>NULL</code> .
required_questions	Vector of character strings. The IDs of questions that must be answered. Defaults to <code>NULL</code> .
all_questions_required	Logical. If <code>TRUE</code> , all questions in the survey will be required. Defaults to <code>FALSE</code> .
start_page	Character string. The ID of the page to start on. Defaults to <code>NULL</code> .
admin_page	Logical. Whether to include an admin page for viewing and downloading survey data. Defaults to <code>FALSE</code> .
auto_scroll	Logical. Whether to enable auto-scrolling to the next question after answering. Defaults to <code>FALSE</code> .
rate_survey	Logical. If <code>TRUE</code> , shows a rating question when exiting the survey. If <code>FALSE</code> , shows a simple confirmation dialog. Defaults to <code>FALSE</code> .
language	Set the language for the survey system messages. Include your own in a <code>translations.yml</code> file, or choose a built in one from the following list: English (<code>"en"</code>), German (<code>"de"</code>), Spanish (<code>"es"</code>), French (<code>"fr"</code>), Italian (<code>"it"</code>). Simplified Chinese (<code>"zh-CN"</code>). Defaults to <code>"en"</code> .

Details

The function performs the following tasks:

- Initializes variables and reactive values.
- Implements conditional display logic for questions.
- Tracks answered questions and updates the progress bar.
- Handles page navigation and skip logic.
- Manages required questions.
- Performs database operation.
- Sets up admin functionality if enabled with the `admin_page` argument.
- Controls auto-scrolling behavior based on the `auto_scroll` argument.
- Uses `sweetalert` for warning messages when required questions are not answered.
- Handles the exit survey process based on the `rate_survey` argument.

Value

This function does not return a value; it sets up the server-side logic for the 'shiny' application.

Progress Bar

The progress bar is updated based on the last answered question. It will jump to the percentage corresponding to the last answered question and will never decrease, even if earlier questions are answered later. The progress is calculated as the ratio of the last answered question's index to the total number of questions.

Database Operations

If db is provided, the function will update the database with survey responses. If db is NULL (ignore mode), responses will be saved to a local CSV file.

Auto-Scrolling

When auto_scroll is TRUE, the survey will automatically scroll to the next question after the current question is answered. This behavior can be disabled by setting auto_scroll = FALSE.

Exit Survey

When rate_survey = TRUE, the function will show a rating question when the user attempts to exit the survey. When FALSE, it will show a simple confirmation dialog. The rating, if provided, is saved with the survey data.

See Also

sd_database(), sd_ui()

Examples

```
if (interactive()) {
  library(surveydown)

  # Get path to example survey file
  survey_path <- system.file("examples", "basic_survey.qmd",
                             package = "surveydown")

  # Copy to a temporary directory
  temp_dir <- tempdir()
  file.copy(survey_path, file.path(temp_dir, "survey.qmd"))
  orig_dir <- getwd()
  setwd(temp_dir)

  # Define a minimal server
  server <- function(input, output, session) {

    # sd_server() accepts these following parameters
    sd_server(
      db = NULL,
```

```
    required_questions = NULL,  
    all_questions_required = FALSE,  
    start_page = NULL,  
    admin_page = FALSE,  
    auto_scroll = FALSE,  
    rate_survey = FALSE,  
    language = "en"  
  )  
}  
  
# Run the app  
shiny::shinyApp(ui = sd_ui(), server = server)  
  
# Clean up  
setwd(orig_dir)  
}
```

sd_setup

Required Set Up Function

Description

This function is depreciated and no longer needed.

Usage

```
sd_setup()
```

Details

The function configures the 'shiny' application to use Bootstrap 5 for styling and enables 'shinyjs' for JavaScript functionalities within the application.

Value

This function does not return a value. It is called for its side effects of setting up the 'shiny' application.

sd_set_password	<i>Set password for surveydown survey</i>
-----------------	---

Description

This function sets your surveydown password, which is used to access the 'PostgreSQL' data (e.g. Supabase). The password is saved in a .Renvirom file and adds .Renvirom to .gitignore.

Usage

```
sd_set_password(password)
```

Arguments

password Character string. The password to be set for the database connection.

Details

The function performs the following actions:

1. Creates a .Renvirom file in the root directory if it doesn't exist.
2. Adds or updates the SURVEYDOWN_PASSWORD entry in the .Renvirom file.
3. Adds .Renvirom to .gitignore if it's not already there.

Value

None. The function is called for its side effects.

Examples

```
## Not run:  
# Set a temporary password for demonstration  
temp_password <- paste0(sample(letters, 10, replace = TRUE), collapse = "")  
  
# Set the password  
sd_set_password(temp_password)  
  
# After restarting R, verify the password was set  
cat("Password is :", Sys.getenv('SURVEYDOWN_PASSWORD'))  
  
## End(Not run)
```

`sd_show_if`*Define show conditions for survey questions*

Description

This function is used to define conditions under which certain questions in the survey should be shown. It takes one or more formulas where the left-hand side is the condition and the right-hand side is the target question ID. If called with no arguments, it will return NULL and set no conditions.

Usage

```
sd_show_if(...)
```

Arguments

... One or more formulas defining show conditions. The left-hand side of each formula should be a condition based on input values, and the right-hand side should be the ID of the question to show if the condition is met.

Value

A list of parsed conditions, where each element contains the condition and the target question ID. Returns NULL if no conditions are provided.

See Also

```
sd_skip_if()
```

Examples

```
if (interactive()) {
  library(surveydown)

  # Get path to example survey file
  survey_path <- system.file("examples", "sd_show_if.qmd",
                             package = "surveydown")

  # Copy to a temporary directory
  temp_dir <- tempdir()
  file.copy(survey_path, file.path(temp_dir, "survey.qmd"))
  orig_dir <- getwd()
  setwd(temp_dir)

  # Define a minimal server
  server <- function(input, output, session) {

    sd_show_if(
      # If "Other" is chosen, show the conditional question
      input$fav_fruit == "other" ~ "fav_fruit_other"
```

```
    )  
    sd_server()  
  }  
  
  # Run the app  
  shiny::shinyApp(ui = sd_ui(), server = server)  
  
  # Clean up  
  setwd(orig_dir)  
}
```

sd_show_password

Show the Saved Survey Password

Description

This function displays the password saved in the `.Renvi ron` file under the `SURVEYDOWN_PASSWORD` variable. It includes a confirmation step to ensure the user wants to display the password in the console. If no password is found, it suggests using the `sd_set_password()` function to define a password.

Usage

```
sd_show_password()
```

Value

A character string containing the password if found and confirmed, or a message if no password is saved along with a suggestion to set one.

Examples

```
## Not run:  
surveydown::sd_show_password()  
  
## End(Not run)
```

`sd_skip_if`*Define skip conditions for survey pages*

Description

This function is used to define conditions under which certain pages in the survey should be skipped. It takes one or more formulas where the left-hand side is the condition and the right-hand side is the target page ID.

Usage

```
sd_skip_if(...)
```

Arguments

... One or more formulas defining skip conditions. The left-hand side of each formula should be a condition based on input values, and the right-hand side should be the ID of the page to skip to if the condition is met.

Value

A list of parsed conditions, where each element contains the condition and the target page ID.

See Also

```
sd_show_if()
```

Examples

```
if (interactive()) {
  library(surveydown)

  # Get path to example survey file
  survey_path <- system.file("examples", "sd_skip_if.qmd",
                             package = "surveydown")

  # Copy to a temporary directory
  temp_dir <- tempdir()
  file.copy(survey_path, file.path(temp_dir, "survey.qmd"))
  orig_dir <- getwd()
  setwd(temp_dir)

  # Define a minimal server
  server <- function(input, output, session) {

    # Skip to page based on input
    sd_skip_if(
      input$fav_fruit == "orange" ~ "orange_page",
      input$fav_fruit == "other" ~ "other_page"
    )
  }
}
```

```
    )  
    sd_server()  
  }  
  
  # Run the app  
  shiny::shinyApp(ui = sd_ui(), server = server)  
  
  # Clean up  
  setwd(orig_dir)  
}
```

sd_store_value	<i>Store a value in the survey data</i>
----------------	---

Description

This function allows storing additional values to be included in the survey data, such as respondent IDs or other metadata.

Usage

```
sd_store_value(value, id = NULL)
```

Arguments

value	The value to be stored. This can be any R object that can be coerced to a character string.
id	(Optional) Character string. The id (name) of the value in the data. If not provided, the name of the value variable will be used.

Value

NULL (invisibly)

Examples

```
if (interactive()) {  
  library(surveydown)  
  
  # Get path to example survey file  
  survey_path <- system.file("examples", "sd_ui.qmd",  
                             package = "surveydown")  
  
  # Copy to a temporary directory  
  temp_dir <- tempdir()  
  file.copy(survey_path, file.path(temp_dir, "basic_survey.qmd"))  
  orig_dir <- getwd()
```

```
setwd(temp_dir)

# Define a minimal server
server <- function(input, output, session) {

  # Create a respondent ID to store
  respondentID <- 42

  # Store the respondentID
  sd_store_value(respondentID)

  # Store the respondentID as the variable "respID"
  sd_store_value(respondentID, "respID")

  sd_server()
}

# Run the app
shiny::shinyApp(ui = sd_ui(), server = server)

# Clean up
setwd(orig_dir)
}
```

sd_ui

Create the UI for a surveydown survey

Description

This function creates the user interface for a surveydown survey, including necessary CSS and JavaScript files, and applies custom styling. It retrieves theme and progress bar settings from the survey.qmd file.

Usage

```
sd_ui()
```

Details

The function reads the following settings from the survey.qmd YAML header:

- `theme`: The theme to be applied to the survey.
- `barcolor`: The color of the progress bar (should be a valid hex color).
- `barposition`: The position of the progress bar ('top', 'bottom', or 'none').

If `barcolor` is not specified or is `NULL`, the default theme color will be used. If `barposition` is not specified, it defaults to 'top'.

Value

A 'shiny' UI object

See Also

sd_server() for creating the server-side logic of the survey

Examples

```
if (interactive()) {
  library(surveydown)

  # Get path to example survey file
  survey_path <- system.file("examples", "sd_ui.qmd",
                             package = "surveydown")

  # Copy to a temporary directory
  temp_dir <- tempdir()
  file.copy(survey_path, file.path(temp_dir, "survey.qmd"))
  orig_dir <- getwd()
  setwd(temp_dir)

  # Define a minimal server
  server <- function(input, output, session) {
    sd_server()
  }

  # Run the app
  shiny::shinyApp(ui = sd_ui(), server = server)

  # Clean up
  setwd(orig_dir)
}
```

sd_version

Check Surveydown Version

Description

This function checks if the local surveydown package is up-to-date with the latest online version. It compares the local version with the latest version available on GitHub and provides information about whether an update is needed.

Usage

sd_version()

Value

No return value, called for side effects (prints version information and update status to the console).

Examples

```
surveydown::sd_version()
```

Index

[sd_add_page](#), 2
[sd_add_question](#), 3
[sd_close](#), 5
[sd_completion_code](#), 6
[sd_copy_value](#), 7
[sd_create_survey](#), 8
[sd_create_translations](#), 9
[sd_database](#), 10
[sd_display_question](#), 11
[sd_display_value](#), 12
[sd_get_data](#), 12
[sd_get_url_pars](#), 13
[sd_include_folder](#), 14
[sd_is_answered](#), 15
[sd_next](#), 16
[sd_output](#), 18
[sd_question](#), 19
[sd_redirect](#), 22
[sd_server](#), 5, 23
[sd_set_password](#), 27
[sd_setup](#), 26
[sd_show_if](#), 28
[sd_show_password](#), 29
[sd_skip_if](#), 30
[sd_store_value](#), 31
[sd_ui](#), 32
[sd_version](#), 33