

# Package ‘tm.plugin.alceste’

February 28, 2025

**Type** Package

**Title** Import Texts from Files in the 'Alceste' Format Using the 'tm'  
Text Mining Framework

**Version** 1.1.2

**Date** 2025-02-27

**Imports** NLP, tm (>= 0.6)

**Suggests** stringi

**Description** Provides a 'tm' Source to create corpora from  
a corpus prepared in the format used by the 'Alceste' application (i.e.  
a single text file with inline meta-data). It is able to import both  
text contents and meta-data (starred) variables.

**License** GPL (>= 2)

**URL** <https://github.com/nalimilan/R.TeMiS>

**BugReports** <https://github.com/nalimilan/R.TeMiS/issues>

**NeedsCompilation** no

**Author** Milan Bouchet-Valat [aut, cre]

**Maintainer** Milan Bouchet-Valat <nalimilan@club.fr>

**Repository** CRAN

**Date/Publication** 2025-02-28 09:50:02 UTC

## Contents

|                                     |   |
|-------------------------------------|---|
| tm.plugin.alceste-package . . . . . | 2 |
| AlcesteSource . . . . .             | 3 |
| readAlceste . . . . .               | 4 |

|              |          |
|--------------|----------|
| <b>Index</b> | <b>5</b> |
|--------------|----------|

tm.plugin.alceste-package

*A plug-in for the tm text mining framework to import corpora from Alceste files*

---

## Description

This package provides a tm Source to create corpora from files formatted in the format used by the Alceste application.

## Details

Typical usage is to create a corpus from an Alceste file prepared manually (here called myAlcesteCorpus.txt). Frequently, it is necessary to specify the encoding of the texts via link{AlcesteSource}'s encoding argument.

```
# Import corpus
source <- europresseSource("myAlcesteCorpus.txt")
corpus <- Corpus(source)

# See how many articles were imported
corpus

# See the contents of the first article and its meta-data
inspect(corpus[1])
meta(corpus[[1]])
```

See link{AlcesteSource} for more details and real examples.

## Author(s)

Milan Bouchet-Valat <nalimilan@club.fr>

## References

<https://image-zafar.com/Logicieluk.html>

---

|               |                       |
|---------------|-----------------------|
| AlcesteSource | <i>Alceste Source</i> |
|---------------|-----------------------|

---

## Description

Construct a source for an input containing a set of texts saved in the Alceste format in a single text file.

## Usage

```
AlcesteSource(x, encoding = "auto")
```

## Arguments

|          |   |
|----------|---|
| x        | Either a character identifying the file or a connection.  |
| encoding | A character string: if non-empty declares the encoding used when reading the file, so the character data can be re-encoded. See the ‘Encoding’ section of the help for <a href="#">file</a> . The default, “auto”, uses <a href="#">stri_enc_detect</a> to try to guess the encoding; this may fail, in which case the native encoding is used. |

## Details

Several texts are saved in a single Alceste-formatted file, separated by lines starting with “\*\*\*” or digits, followed by starred variables (see links below). These variables are set as document meta-data that can be accessed via the [meta](#) function.

Currently, “theme” lines starting with “-\*” are ignored.

## Value

An object of class `AlcesteSource` which extends the class `Source` representing set of articles from Alceste.

## Author(s)

Milan Bouchet-Valat

## See Also

[https://image-zafar.com/sites/default/files/telechargements/formatage\\_alceste.pdf](https://image-zafar.com/sites/default/files/telechargements/formatage_alceste.pdf)  
(in French) about the Alceste format

[readAlceste](#) for the function actually parsing individual articles.

[getSources](#) to list available sources.

## Examples

```
library(tm)
file <- system.file("texts", "alceste_test.txt",
                    package = "tm.plugin.alceste")
corpus <- Corpus(AlcesteSource(file))

# See the contents of the documents
inspect(corpus)

# See meta-data associated with first article
meta(corpus[[1]])
```

---

|             |   |
|-------------|---|
| readAlceste | <i>Read in a text in the Alceste format</i> |
|-------------|---|

---

## Description

Read in a text in the Alceste format using starred variables.

## Usage

```
readAlceste(elem, language, id)
```

## Arguments

|          |   |
|----------|---|
| elem     | A list with the named element content which must hold the document to be read in.   |
| language | A character vector giving the text's language. If set to NA, the language will automatically be set to the value reported in the document (which is usually correct). |
| id       | A character vector representing a unique identification string for the returned text document.  |

## Value

A PlainTextDocument with the contents of the article and the available meta-data set.

## Author(s)

Milan Bouchet-Valat

## See Also

[getReaders](#) to list available reader functions.

# Index

AlcesteSource, [3](#)

eoi.AlcesteSource (AlcesteSource), [3](#)

file, [3](#)

getElem.AlcesteSource (AlcesteSource), [3](#)

getReaders, [4](#)

getSources, [3](#)

meta, [3](#)

readAlceste, [3](#), [4](#)

stri\_enc\_detect, [3](#)

tm.plugin.alceste

(tm.plugin.alceste-package), [2](#)

tm.plugin.alceste-package, [2](#)