

Package ‘tmle’

October 15, 2019

Version 1.4.0.1

Date 2019-10-15

Title Targeted Maximum Likelihood Estimation

Author Susan Gruber [aut, cre],
Mark van der Laan [aut],
Chris Kennedy [ctr]

Maintainer Susan Gruber <sgruber@cal.berkeley.edu>

Copyright Copyright 2012. The Regents of the University of California
(Regents). All Rights Reserved.

Depends glmnet, SuperLearner (>= 2.0)

Suggests dbarts (>= 0.9-12), gam (>= 1.15)

Description

Targeted maximum likelihood estimation of point treatment effects (Targeted Maximum Likelihood Learning, The International Journal of Biostatistics, 2(1), 2006. This version automatically estimates the additive treatment effect among the treated (ATT) and among the controls (ATC). The tmle() function calculates the adjusted marginal difference in mean outcome associated with a binary point treatment, for continuous or binary outcomes. Relative risk and odds ratio estimates are also reported for binary outcomes. Missingness in the outcome is allowed, but not in treatment assignment or baseline covariate values. The population mean is calculated when there is missingness, and no variation in the treatment assignment. The tmleMSM() function estimates the parameters of a marginal structural model for a binary point treatment effect. Effect estimation stratified by a binary mediating variable is also available. An ID argument can be used to identify repeated measures. Default settings call 'SuperLearner' to estimate the Q and g portions of the likelihood, unless values or a user-supplied regression function are passed in as arguments.

License BSD_3_clause + file LICENSE | GPL-2

URL <https://CRAN.R-project.org/package=tmle>

NeedsCompilation no

Repository CRAN

Date/Publication 2019-10-15 15:40:02 UTC

R topics documented:

tmle-package	2
calcParameters	3
calcSigma	4
estimateG	6
estimateQ	7
fev	8
oneStepATT	9
summary.tmle	10
summary.tmleMSM	12
tmle	13
tmle.SL.dbarts2	18
tmleMSM	20
tmleNews	24

Index	25
--------------	-----------

tmle-package	<i>Targeted Maximum Likelihood Estimation with Super Learning</i>
--------------	---

Description

Targeted maximum likelihood estimation of marginal treatment effect of a binary point treatment on a continuous or binary outcome, adjusting for baseline covariates (ATE: entire population, ATT: treated population, ATC: control population). Missingness in the outcome is accounted for in the estimation procedure. The population mean outcome is calculated when there is missingness and no treatment. Controlled direct effect estimation is available, and MSM parameter estimation for binary point treatment effects. Optional data-adaptive estimation of Q and g portions of the likelihood using the SuperLearner package is strongly encouraged.

Details

Package:	tmle
Type:	Package
Version:	1.4.0.1
Date:	2019-10-15
License:	BSD GPL-2

Author(s)

Susan Gruber, in collaboration with Mark van der Laan.

Maintainer: Susan Gruber, <sgruber@cal.berkeley.edu>

References

1. Gruber, S. and van der Laan, M.J. (2012), tml: An R Package for Targeted Maximum Likelihood Estimation. *Journal of Statistical Software*, 51(13), 1-35. <http://www.jstatsoft.org/v51/i13/>
2. Gruber, S. and van der Laan, M.J. (2009), Targeted Maximum Likelihood Estimation: A Gentle Introduction. *U.C. Berkeley Division of Biostatistics Working Paper Series*. Working Paper 252. <http://www.bepress.com/ucbbiostat/paper252>
3. Gruber, S. and van der Laan, M.J. (2010), A Targeted Maximum Likelihood Estimator of a Causal Effect on a Bounded Continuous Outcome. *The International Journal of Biostatistics*, 6(1), 2010.
4. Rosenblum, M. and van der Laan, M.J. (2010). Targeted Maximum Likelihood Estimation of the Parameter of a Marginal Structural Model. *The International Journal of Biostatistics*, 6(2), 2010.
5. van der Laan, M.J. and Rubin, D. (2006), Targeted Maximum Likelihood Learning. *The International Journal of Biostatistics*, 2(1). <http://www.bepress.com/ijb/vol2/iss1/11/>
6. van der Laan, M.J., Rose, S., and Gruber, S., editors, (2009) Readings in Targeted Maximum Likelihood Estimation. *U.C. Berkeley Division of Biostatistics Working Paper Series*. Working Paper 254. <http://www.bepress.com/ucbbiostat/paper254>
7. van der Laan, M.J. and Gruber S. (2016), One-Step Targeted Minimum Loss-based Estimation Based on Universal Least Favorable One-Dimensional Submodels. *The International Journal of Biostatistics*, 12 (1), 351-378.

See Also

[tml](#), [tmlMSM](#)

calcParameters

Calculate Parameter Estimates (calcParameters)

Description

An internal function called by the `tml` function to calculate the population mean effect when there is missingness in the data, but no treatment assignment. When observations are in treatment and control groups, estimates the additive treatment effect among the entire population (ATE), among the treated (ATT), and among the controls (ATC). If the outcome is binary, also the relative risk and odds ratio parameters. P-values and 95% confidence intervals are also calculated (on the log scale for RR and OR).

Usage

```
calcParameters(Y, A, I.Z, Delta, g1W, g0W, Q, mu1, mu0, id, family)
```

Arguments

Y	continuous or binary outcome variable
A	binary treatment indicator, 1 - treatment, 0 - control
I.Z	Indicator $Z=z$, needed for CDE estimation
Delta	indicator of missing outcome. 1 - observed, 0 - missing
g1W	censoring mechanism estimates, $P(A = 1 W) * P(Delta = 1 A, W)$
g0W	censoring mechanism estimates, $P(A = 0 W) * P(Delta = 1 A, W)$
Q	a 3-column matrix ($Q(A, W), Q(1, W), Q(0, W)$)
mu1	targeted estimate of $E(Y A = 1, W)$
mu0	targeted estimate of $E(Y A = 0, W)$
id	subject identifier
family	family specification for regressions, generally 'gaussian' for continuous outcomes, 'binomial' for binary outcomes

Value

EY1	Population mean outcome estimate, variance, p-value, 95% confidence interval (missingness only, no treatment assignment), or NULL
ATE	additive treatment effect estimate, variance, p-value, 95% confidence interval, or NULL
RR	relative risk estimate, p-value, 95% confidence interval, $\log(RR)$, $\text{variance}(\log(RR))$, or NULL
OR	odds ratio estimate, p-value, 95% confidence interval, $\log(OR)$, $\text{variance}(\log(OR))$, or NULL

Author(s)

Susan Gruber

See Also

[tmle](#), [estimateQ](#), [estimateG](#), [tmleMSM](#), [calcSigma](#)

calcSigma	<i>Calculate Variance-Covariance Matrix for MSM Parameters (calcSigma)</i>
-----------	--

Description

An internal function called by the `tmleMSM` function to calculate the variance-covariance matrix of the parameter estimates based on the influence curve of the specified MSM.

Usage

```
calcSigma(hAV, gAVW, Y, Q, mAV, covar.MSM, covar.MSMA0, covar.MSMA1, I.V,
          Delta, ub, id, family)
```

Arguments

hAV	values used in numerator of weights applied to the estimation procedure
gAVW	$p(A = a V, W, T) * p(Delta = 1 A, V, W, T)$
Y	continuous or binary outcome variable
Q	estimated $P(Y A, V, W, T, Delta = 1)$, typically targeted values Q^* are passed in
mAV	predicted values for $EY1$ from the MSM using the targeted estimates for psi
covar.MSM	covariate values used as predictors for the MSM when $A=a$
covar.MSMA0	covariate values used as predictors for the MSM when $A=0$
covar.MSMA1	covariate values used as predictors for the MSM when $A=1$
I.V	indicator that observation is in stratum of interest
Delta	indicator of missing outcome. 1 - observed, 0 - missing
ub	upper bound on weights
id	subject identifier
family	'gaussian' for continuous outcomes, 'binomial' for binary outcomes

Value

sigma	influence-curve based variance-covariance matrix. See Rosenblum&vanderLaan2010 for details.
-------	---

Author(s)

Susan Gruber

See Also

[tmle](#), [estimateQ](#), [estimateG](#), [tmleMSM](#)

Description

An internal function called by the `tmle` function to obtain an estimate of conditional treatment assignment probabilities $P(A = 1|W)$, and conditional probabilities for missingness, $P(Delta = 1|A, W)$. The estimate can be based on user-supplied values, a user-supplied regression formula, or a data-adaptive super learner fit. If the SuperLearner package is not available, and there are no user-specifications, estimation is carried out using main terms regression with `glm`. These main terms-based estimates may yield poor results.

Usage

```
estimateG(d, g1W, gform, SL.library, id, V, verbose, message,
outcome, newdata=d, discreteSL)
```

Arguments

<code>d</code>	dataframe with binary dependent variable in the first column, predictors in remaining columns
<code>g1W</code>	vector of values for $P(A = 1 W)$, $P(Z = 1 A, W)$, or $P(Delta = 1 Z, A, W)$
<code>gform</code>	regression formula of the form $A \sim W1$, (dependent variable is one of A, Z, D) if specified this overrides the call to SuperLearner
<code>SL.library</code>	vector of prediction algorithms used by SuperLearner, default value is ('SL.glm', 'tmle.SL.dbarts.k.5', 'SL.gam')
<code>id</code>	subject identifier
<code>V</code>	Number of cross validation folds for Super Learning
<code>verbose</code>	status messages printed if set to TRUE
<code>message</code>	text specifies whether treatment or missingness mechanism is being estimated
<code>outcome</code>	A, D, Z to indicate which quantity is being estimated.
<code>newdata</code>	optional dataset to be used for prediction after fitting on <code>d</code> .
<code>discreteSL</code>	If true, returns discrete SL estimates, otherwise ensemble estimates. Ignored when SL is not used.

Value

<code>g1W</code>	a vector containing values for $P(A = 1 W)$, matrix for $P(Z = 1 A, W)$, evaluated at $A=0, A=1$, or matrix $P(Delta = 1 Z, A, W)$ evaluated at $(0,0), (0,1), (1,0), (1,1)$
<code>coef</code>	coefficients for each term in the working model used for estimation if <code>glm</code> was used
<code>type</code>	estimation procedure

Author(s)

Susan Gruber

See Also[tmle](#), [estimateQ](#), [calcParameters](#), [tmleMSM](#), [calcSigma](#)

estimateQ

*Initial Estimation of Q portion of the Likelihood***Description**

An internal function called by the `tmle` function to obtain an initial estimate of the Q portion of the likelihood based on user-supplied matrix values for predicted values of (counterfactual outcomes) $Q(\theta, W)$, $Q(1, W)$, or a user-supplied regression formula, or based on a data-adaptively selected SuperLearner fit. In the absence of user-supplied values, a user-supplied regression formula takes precedence over data-adaptive super-learning. The default is to return cross-validated predictions.

Usage

```
estimateQ(Y, Z, A, W, Delta, Q, Qbounds, Qform, maptoYstar, SL.library, cvQinit,
         family, id, V, verbose, discreteSL)
```

Arguments

Y	continuous or binary outcome variable
Z	optional binary indicator for intermediate covariate for controlled direct effect estimation
A	binary treatment indicator, 1 - treatment, 0 - control
W	vector, matrix, or dataframe containing baseline covariates
Delta	indicator of missing outcome. 1 - observed, 0 - missing
Q	3-column matrix ($Q(A, W)$, $Q(\theta, W)$, $Q(1, W)$)
Qbounds	Bounds on predicted values for Q, set to alpha for logistic fluctuation, or range(Y) if not user-supplied
Qform	regression formula of the form $Y \sim A + W$
maptoYstar	if TRUE indicates continuous Y values should be shifted and scaled to fall between (0,1)
SL.library	specification of prediction algorithms, default is ('SL.glm', 'SL.glmnet', 'tmle.SL.dbarts2'). In practice, including more prediction algorithms in the library improves results.
cvQinit	logical, whether or not to estimate cross-validated values for initial Q, default=TRUE
family	family specification for regressions, generally 'gaussian' for continuous outcomes, 'binomial' for binary outcomes

id	subject identifier
V	Number of cross-validation folds for Super Learning
verbose	status message printed if set to TRUE
discreteSL	If true, returns discrete SL estimates, otherwise ensemble estimates. Ignored when SL is not used.

Value

Q	$n \times 3$ matrix, columns contain the initial estimate of $[Q(A, W) = E(Y A = a, W), Q(0, W) = E(Y A = 0, W), Q(1, W) = E(Y A = 1, W)]$. For controlled direct estimation, $n \times 5$ matrix, $E(Y Z, A, W)$, evaluated at $(z, a), (0, 0), (0, 1), (1, 0), (1, 1)$ on scale of linear predictors
Qfamily	‘binomial’ for targeting with logistic fluctuation, ‘gaussian’ for linear fluctuation
coef	coefficients for each term in working model used for initial estimation of Q if glm used.
type	type of estimation procedure

Author(s)

Susan Gruber

See Also

[tmle](#), [estimateG](#), [calcParameters](#), [tmleMSM](#), [calcSigma](#)

fev	<i>Forced Expiratory Volume (FEV) Data (fev)</i>
-----	--

Description

Sample of 654 youths, aged 3 to 19, in the area of East Boston during middle to late 1970’s. Interest concerns the relationship between smoking and FEV. Since the study is necessarily observational, statistical adjustment via regression models clarifies the relationship.

Usage

```
data(fev)
```

Format

A data frame with 654 observations on the following 5 variables.

age a numeric vector
 fev a numeric vector
 ht a numeric vector
 sex a numeric vector
 smoke a numeric vector

Source

Kahn M (2005). An Exhale Problem for Teaching Statistics. The Journal of Statistical Education, 13(2).
 Rosner, B. (1999), Fundamentals of Biostatistics, 5th Ed., Pacific Grove, CA: Duxbury.

oneStepATT	<i>Calculate Additive treatment effect among the treated (oneStepATT)</i>
------------	---

Description

An internal function called by the `tmle` function to calculate the additive treatment effect among the treated (ATT) using a universal least favorable submodel (on the transformed scale if outcomes are continuous). The function is called a second time with updated arguments to calculate the additive treatment effect among the controls (ATC). Missingness in the outcome data is allowed.

Usage

```
oneStepATT(Y, A, Delta, Q, g1W, pDelta1, depsilon, max_iter, gbounds, Qbounds)
```

Arguments

Y	continuous or binary outcome variable
A	binary treatment indicator, 1 - treatment, 0 - control
Delta	indicator of missing outcome. 1 - observed, 0 - missing
Q	a 3-column matrix $(Q(A, W), Q(1, W), Q(0, W))$
g1W	treatment mechanism estimates, $P(A = 1 W)$
pDelta1	censoring mechanism estimates, a 2-column matrix $[P(Delta = 1 A = 0, W), P(Delta = 1 A = 1, W)]$
depsilon	step size for delta moves, set to 0.001
max_iter	maximum number of iterations before terminating without convergence
gbounds	bounds on the propensity score for untreated subjects
Qbounds	alpha bounds on the logit scale

Value

psi	effect estimate (on the transformed scale for continuous outcomes)
IC	influence function
conv	TRUE if procedure converged, FALSE otherwise

Author(s)

Susan Gruber

See Also

[tmle](#),

summary.tmle

*Summarization of the results of a call to the tmle routine***Description**

These functions are all [methods](#) for class tmle, tmle.list, summary.tmle, summary.tmle.list objects

Usage

```
## S3 method for class 'tmle'
summary(object, ...)
## S3 method for class 'tmle.list'
summary(object, ...)
## S3 method for class 'tmle'
print(x, ...)
## S3 method for class 'tmle.list'
print(x, ...)
## S3 method for class 'summary.tmle'
print(x, ...)
## S3 method for class 'summary.tmle.list'
print(x, ...)
```

Arguments

object	an object of class tmle or tmle.list.
x	an object of class tmle or tmle.list for summary functions, class summary.tmle or summary.tmle.list for print functions.
...	currently ignored.

Details

print.tmle prints the estimate, variance, p-value, and 95% confidence interval only. print.summary.tmle, called indirectly by entering the command summary(result) (where result has class tmle), outputs additional information. Controlled direct effect estimates have class tmle.list, a list of two objects of class tmle. The first item corresponds to $Z = 0$, the second to $Z = 1$

Value

estimates	list of parameter estimates, pvalues, and 95% confidence intervals
Qmodel	working model used to obtain initial estimate of Q portion of the likelihood, if glm used
Qterms	terms in the model for Q
Qcoef	coefficient of each term in model for Q
gmodel	model used to estimate treatment mechanism g

gterms	terms in the treatment mechanism model
gcoef	coefficient of each term in model for treatment mechanism
gtype	description of estimation procedure for treatment mechanism, e.g. "SuperLearner"
gdiscreteSL	flag indicating whether discrete SL or ensemble SL was used for treatment mechanism estimation
g.Zmodel	model used to estimate intermediate variable assignment mechanism g.Z
g.Zterms	terms in the intermediate mechanism model
g.Zcoef	coefficient of each term in model for intermediate mechanism
g.Ztype	description of estimation procedure for intermediate variable
g.ZdiscreteSL	flag indicating whether discrete SL or ensemble SL was used for intermediate variable estimation
g.Deltamodel	model used to estimate missingness mechanism g.Delta
g.Deltaterms	terms in the missingness mechanism model
g.Deltacoef	coefficient of each term in model for missingness mechanism
g.Deltatype	description of estimation procedure for missingness
g.DeltadiscreteSL	flag indicating whether discrete SL or ensemble SL was used for missingness estimation

Author(s)

Susan Gruber

See Also[tmle](#)**Examples**

```
# generate data
set.seed(10)
n <- 500
W <- matrix(rnorm(n*3), ncol=3)
A <- rbinom(n,1, 1/(1+exp(-(.1*W[,1] - .1*W[,2] + .5*W[,3])))
Y <- A + 2*W[,1] + W[,3] + W[,2]^2 + rnorm(n)
colnames(W) <- paste("W",1:3, sep="")

result <- tmle(Y,A,W, Qform="Y~A+W1", g1W=rep(.5, n))
summary(result)
```

summary.tmleMSM

*Summarization of the results of a call to the tmleMSM function***Description**

These functions are all [methods](#) for class tmleMSM, summary.tmleMSM objects

Usage

```
## S3 method for class 'tmleMSM'
summary(object, ...)
## S3 method for class 'tmleMSM'
print(x, ...)
## S3 method for class 'summary.tmleMSM'
print(x, ...)
```

Arguments

object	an object of class tmleMSM.
x	an object of class tmleMSM for summary functions, class summary.tmleMSM for print functions.
...	currently ignored.

Details

print.tmleMSM prints the estimate, standard error, p-value, and 95% confidence interval only. print.summary.tmleMSM, called indirectly by entering the command summary(result) (where result has class tmleMSM), outputs additional information.

Value

estimates	matrix of MSM parameter estimates, standard errors, pvalues, upper and lower bounds on 95% confidence intervals
sigma	variance-covariance matrix
Qmodel	working model used to obtain initial estimate of Q portion of the likelihood, if glm used
Qterms	terms in the model for Q
Qcoef	coefficient of each term in model for Q
gmodel	model used to estimate treatment mechanism g
gterms	terms in the treatment mechanism model
gcoef	coefficient of each term in model for treatment mechanism
gtype	description of estimation procedure for treatment mechanism, e.g. "SuperLearner"
g.AVmodel	model used to estimate $h(A,V)$ (or $h(A,T)$)
g.AVterms	terms in the model for $h(A,V)$

<code>g.AVcoef</code>	coefficient of each term in model for $h(A,V)$
<code>g.AVtype</code>	description of estimation procedure for $h(A,V)$
<code>g.Deltamodel</code>	model used to estimate missingness mechanism $g.Delta$
<code>g.Deltaterms</code>	terms in the missingness mechanism model
<code>g.Deltacoef</code>	coefficient of each term in model for missingness mechanism
<code>g.Deltatype</code>	description of estimation procedure for missingness
<code>psi.Qinit</code>	MSM parameter estimates based on initial (untargeted) estimated Q

Author(s)

Susan Gruber

See Also[tmleMSM](#)

`tmle`*Targeted Maximum Likelihood Estimation*

Description

Targeted maximum likelihood estimation of parameters of a marginal structural model, and of marginal treatment effects of a binary point treatment on an outcome. In addition to the additive treatment effect, risk ratio and odds ratio estimates are reported for binary outcomes. The `tmle` function is generally called with arguments (Y,A,W) , where Y is a continuous or binary outcome variable, A is a binary treatment variable, ($A=1$ for treatment, $A=0$ for control), and W is a matrix or dataframe of baseline covariates. The population mean outcome is calculated when there is no variation in A . If values of binary mediating variable Z are supplied, estimates are returned at each level of Z . Missingness in the outcome is accounted for in the estimation procedure if missingness indicator Δ is 0 for some observations. Repeated measures can be identified using the `id` argument.

Usage

```
tmle(Y, A, W, Z=NULL, Delta = rep(1,length(Y)), Q = NULL, Q.Z1 = NULL, Qform = NULL,
     Qbounds = NULL, Q.SL.library = c("SL.glm", "tmle.SL.dbarts2", "SL.glmnet"),
     cvQinit = TRUE, g1W = NULL, gform = NULL, gbound = 0.025, pZ1=NULL,
     g.Zform = NULL, pDelta1 = NULL, g.Deltaform = NULL,
     g.SL.library = c("SL.glm", "tmle.SL.dbarts.k.5", "SL.gam"),
     family = "gaussian", fluctuation = "logistic", alpha = 0.9995, id=1:length(Y), V = 5,
     verbose = FALSE, Q.discreteSL=FALSE, g.discreteSL=FALSE, prescreenW.g=TRUE,
     min.retain = 2, target.gwt = TRUE, automate=FALSE)
```

Arguments

Y	continuous or binary outcome variable
A	binary treatment indicator, 1 - treatment, 0 - control
W	vector, matrix, or dataframe containing baseline covariates
Z	optional binary indicator for intermediate covariate for controlled direct effect estimation
Delta	indicator of missing outcome or treatment assignment. 1 - observed, 0 - missing
Q	optional $n \times 2$ matrix of initial values for Q portion of the likelihood, $(E(Y A = 0, W), E(Y A = 1, W))$
Q.Z1	optional $n \times 2$ matrix of initial values for Q portion of the likelihood, $(E(Y Z = 1, A = 0, W), E(Y Z = 1, A = 1, W))$. (When specified, values for $E(Y Z = 0, A = 0, W), E(Y Z = 0, A = 1, W)$ are passed in using the Q argument
Qform	optional regression formula for estimation of $E(Y A, W)$, suitable for call to <code>glm</code>
Qbounds	vector of upper and lower bounds on Y and predicted values for initial Q. Defaults to the range of Y, widened by 10% of the min and max values.
Q.SL.library	optional vector of prediction algorithms to use for SuperLearner estimation of initial Q
cvQinit	logical, if TRUE, estimates cross-validated predicted values, default=TRUE
g1W	optional vector of conditional treatment assignment probabilities, $P(A = 1 W)$
gform	optional regression formula of the form $A \sim W$, if specified this overrides the call to SuperLearner
gbound	value between (0,1) for truncation of predicted probabilities. See Details section for more information
pZ1	optional $n \times 2$ matrix of conditional probabilities $P(Z = 1 A = 0, W), P(Z = 1 A = 1, W)$
g.Zform	optional regression formula of the form $Z \sim A + W$, if specified this overrides the call to SuperLearner
pDelta1	optional matrix of conditional probabilities for missingness mechanism, $n \times 2$ when Z is NULL $P(Delta = 1 A = 0, W), P(Delta = 1 A = 1, W)$. $n \times 4$ otherwise, $P(Delta = 1 Z = 0, A = 0, W), P(Delta = 1 Z = 0, A = 1, W), P(Delta = 1 Z = 1, A = 0, W), P(Delta = 1 Z = 1, A = 1, W)$
g.Deltaform	optional regression formula of the form $Delta \sim A + W$, if specified this overrides the call to SuperLearner
g.SL.library	optional vector of prediction algorithms to use for SuperLearner estimation of <code>g1W</code> or <code>pDelta1</code>
family	family specification for working regression models, generally 'gaussian' for continuous outcomes (default), 'binomial' for binary outcomes
fluctuation	'logistic' (default), or 'linear'
alpha	used to keep predicted initial values bounded away from (0,1) for logistic fluctuation

<code>id</code>	optional subject identifier
<code>V</code>	Number of cross-validation folds for estimating Q, and for super learner estimation of g
<code>verbose</code>	status messages printed if set to TRUE (default=FALSE)
<code>Q.discreteSL</code>	if TRUE, discreteSL is used instead of ensemble SL. Ignored when SL not used to estimate Q
<code>g.discreteSL</code>	if TRUE, discreteSL is used instead of ensemble SL. Ignored when SL not used to estimate Q
<code>prescreenW.g</code>	Screen covariates before estimating g in order to retain only those associated with Stage 1 residuals
<code>min.retain</code>	Minimum number of covariates to retain when prescreening covariates for g. Ignored when <code>prescreenW.g=FALSE</code>
<code>target.gwt</code>	When TRUE, move g from denominator of clever covariate to the weight when fitting epsilon
<code>automate</code>	When TRUE, all tuning parameters are set to their default values. Number of cross validation folds and truncation level for g are set data-adaptively based on sample size (see details).

Details

`gbounds` defaults to (0.025, 0.975) for treatment effect estimates. If only one value is provided, symmetric truncation levels are assumed. Bounds default to (0.025, 1) for estimating the population mean outcome.

`W` should only contain covariates that are factors when Super Learner is not used to estimate Q or g.

Controlled direct effects are estimated when binary covariate Z is non-null. The `tmle` function returns an object of class `tmle.list`, a list of two items of class `tmle`. The first corresponds to estimates obtained when Z is fixed at 0, the second corresponds to estimates obtained when Z is fixed at 1.

When `automate = TRUE` the sample size determines the number of cross validation folds, `V`, and the bound on g as follows: When $n \leq 100$, $V=20$ and $gbd = 0.1$; When $100 < n \leq 500$ $V=10$, $gbd = 0.05$; When $500 < n \leq 1000$ $V=5$, $gbd = 0.025$; When $1000 < n \leq 10000$ $V=3$, $gbd = 0.025$; When $n > 10000$ $V=2$, $gbd = 0.01$.

Value

<code>estimates</code>	list with elements EY1 (population mean), ATE (additive treatment effect), ATT (additive treatment effect among the treated), ATC (additive treatment effect among the controls), RR (relative risk), OR (odds ratio). Each element in the estimates of these is itself a list containing <ul style="list-style-type: none"> • <code>psi</code> - parameter estimate • <code>pvalue</code> - two-sided p-value • <code>CI</code> - 95% confidence interval • <code>var.psi</code> - Influence-curve based variance of estimate (ATE parameter only) • <code>log.psi</code> - Parameter estimate on log scale (RR and OR parameters)
------------------------	--

- var.log.psi - Influence-curve based variance of estimate on log scale (RR and OR parameters)

Qinit	initial estimate of Q. Qinit\$coef are the coefficients for a glm model for Q, if applicable. Qinit\$Q is an $n \times 2$ matrix, where n is the number of observations. Columns contain predicted values for $Q(\theta, W)$, $Q(1, W)$ using the initial fit. Qinit\$type is method for estimating Q
Qstar	targeted estimate of Q, an $n \times 2$ matrix with predicted values for $Q(\theta, W)$, $Q(1, W)$ using the updated fit
g	treatment mechanism estimate. A list with four items: g\$g1W contains estimates of $P(A = 1 W)$ for each observation, g\$coef the coefficients for the model for g when glm used, g\$type estimation procedure, g\$discreteSL flag
g.Z	intermediate covariate assignment estimate (when applicable). A list with four items: g.Z\$g1W an $n \times 2$ matrix containing values of $P(Z = 1 A = 1, W)$, $P(Z = 1 A = 0, W)$ for each observation, g.Z\$coef the coefficients for the model for g when glm used, g.Z\$type estimation procedure, g.Z\$discreteSL flag
g.Delta	missingness mechanism estimate. A list with four items: g.Delta\$g1W an $n \times 4$ matrix containing values of $P(\Delta = 1 Z, A, W)$ for each observation, with $(Z=0, A=0)$, $(Z=0, A=1)$, $(Z=1, A=0)$, $(Z=1, A=1)$. (When Z is NULL, columns 3 and 4 are duplicates of 1 and 2.) g.Delta\$coef the coefficients for the model for g when glm used, g.Delta\$type estimation procedure, g.Delta\$discreteSL flag
gbound	bounds used to truncate g
W.retained	names of covariates used to model the components of g

Author(s)

Susan Gruber <sgruber@cal.berkeley.edu>, in collaboration with Mark van der Laan.

References

1. Gruber, S. and van der Laan, M.J. (2012), tmle: An R Package for Targeted Maximum Likelihood Estimation. *Journal of Statistical Software*, 51(13), 1-35. <http://www.jstatsoft.org/v51/i13/>
2. Gruber, S. and van der Laan, M.J. (2009), Targeted Maximum Likelihood Estimation: A Gentle Introduction. *U.C. Berkeley Division of Biostatistics Working Paper Series*. Working Paper 252. <http://www.bepress.com/ucbbiostat/paper252>
3. Gruber, S. and van der Laan, M.J. (2010), A Targeted Maximum Likelihood Estimator of a Causal Effect on a Bounded Continuous Outcome. *The International Journal of Biostatistics*, 6(1), 2010.
4. Rosenblum, M. and van der Laan, M.J. (2010). Targeted Maximum Likelihood Estimation of the Parameter of a Marginal Structural Model. *The International Journal of Biostatistics*, 6(2), 2010.
5. van der Laan, M.J. and Rubin, D. (2006), Targeted Maximum Likelihood Learning. *The International Journal of Biostatistics*, 2(1). <http://www.bepress.com/ijb/vol2/iss1/11/>
6. van der Laan, M.J., Rose, S., and Gruber, S., editors, (2009) Readings in Targeted Maximum Likelihood Estimation. *U.C. Berkeley Division of Biostatistics Working Paper Series*. Working Paper 254. <http://www.bepress.com/ucbbiostat/paper254>

7. van der Laan, M.J. and Gruber S. (2016), One-Step Targeted Minimum Loss-based Estimation Based on Universal Least Favorable One-Dimensional Submodels. *The International Journal of Biostatistics*, 12 (1), 351-378.

See Also

[summary.tmle](#), [estimateQ](#), [estimateG](#), [calcParameters](#), [oneStepATT](#), [tmleMSM](#), [calcSigma](#)

Examples

```
library(tmle)
set.seed(1)
n <- 250
W <- matrix(rnorm(n*3), ncol=3)
A <- rbinom(n,1, 1/(1+exp(-(.2*W[,1] - .1*W[,2] + .4*W[,3])))
Y <- A + 2*W[,1] + W[,3] + W[,2]^2 + rnorm(n)

# Example 1. Simplest function invocation
# SuperLearner called to estimate Q, g
# Delta defaults to 1 for all observations
## Not run:
result1 <- tmle(Y,A,W)
summary(result1)

## End(Not run)
# Example 2:
# User-supplied regression formulas to estimate Q and g
# binary outcome
n <- 250
W <- matrix(rnorm(n*3), ncol=3)
colnames(W) <- paste("W",1:3, sep="")
A <- rbinom(n,1, plogis(0.6*W[,1] +0.4*W[,2] + 0.5*W[,3]))
Y <- rbinom(n,1, plogis(A + 0.2*W[,1] + 0.1*W[,2] + 0.2*W[,3]^2 ))
result2 <- tmle(Y,A,W, family="binomial", Qform=Y~A+W1+W2+W3, gform=A~W1+W2+W3)
summary(result2)

## Not run:
# Example 3: Population mean outcome
# User-supplied (misspecified) model for Q,
# Super learner called to estimate g, g.Delta
# V set to 2 for demo, not recommended at this sample size
# approx. 20
Y <- W[,1] + W[,2]^2 + rnorm(n)
Delta <- rbinom(n, 1, 1/(1+exp(-(1.7-1*W[,1])))
result3 <- tmle(Y,A=NULL,W, Delta=Delta, Qform="Y~A+W1+W2+W3", V=2)
print(result3)

# Example 4: Controlled direct effect
# User-supplied models for g, g.Z
# V set to 2 for demo, not recommended at this sample size
A <- rbinom(n,1,.5)
Z <- rbinom(n, 1, plogis(.5*A + .1*W[,1]))
```

```

Y <- 1 + A + 10*Z + W[,1]+ rnorm(n)

CDE <- tmle(Y,A,W, Z, gform="A~1", g.Zform = "Z ~ A + W1", V=2)
print(CDE)
total.effect <- tmle(Y,A, W, gform="A~1")
print(total.effect)

## End(Not run)

```

tmle.SL.dbarts2	<i>Super Learner wrappers for modeling and prediction using bart in the dbarts package</i>
-----------------	--

Description

These functions are used internally, not typically called by the user

Usage

```

tmle.SL.dbarts2(Y, X, newX, family, obsWeights, id, sigest = NA, sigdf = 3,
sigquant = 0.90, k = 2, power = 2.0, base = 0.95, binaryOffset = 0.0,
ntree = 200, ndpost = 1000, nskip = 100, printevery = 100, keepevery = 1,
keeptrainfits = TRUE, usequants = FALSE, numcut = 100, printcutoffs = 0,
nthread = 1, keepcall = TRUE, verbose = FALSE, ...)
tmle.SL.dbarts.k.5(Y, X, newX, family, obsWeights, id, sigest = NA, sigdf = 3,
sigquant = 0.90, k = 0.5, power = 2.0, base = 0.95, binaryOffset = 0.0,
ntree = 200, ndpost = 1000, nskip = 100, printevery = 100, keepevery = 1,
keeptrainfits = TRUE, usequants = FALSE, numcut = 100, printcutoffs = 0,
nthread = 1, keepcall = TRUE, verbose = FALSE, ...)
## S3 method for class 'tmle.SL.dbarts2'
predict(object, newdata, family, ...)

```

Arguments

Y	Dependent variable
X	Predictor covariate matrix or data frame used as training set
newX	Predictor covariate matrix or data frame for which predictions should be made
family	Regression family, 'gaussian' or 'binomial'
obsWeights	observation-level weights
id	idid to group observations, not used
sigest	An estimate of error variance. See bart documentation
sigdf	Degrees of freedom for error variance prior. See bart documentation
sigquant	Quantile of error variance prior. See bart documentation
k	Tuning parameter that controls smoothing. Larger values are more conservative, see Details

power	Power parameter for tree prior
base	Base parameter for tree prior
binaryOffset	Allows fits with probabilities shrunk towards values other than 0.5. See bart documentation
ntree	Number of trees in the sum-of-trees formulation
ndpost	Number of posterior draws after burn in
nskip	Number of MCMC iterations treated as burn in
printevery	How often to print messages
keepevery	Every keepevery draw is kept to be returned to the user
keeptrainfits	If TRUE the draws of $f(x)$ for x corresponding to the rows of <code>x.train</code> are returned
usequants	Controls how tree decisions rules are determined. See bart documentation
numcut	Maximum number of possible values used in decision rules
printcutoffs	Number of cutoff rules to print to screen. 0 prints nothing
nthread	Integer specifying how many threads to use
keepcall	Returns the call to BART when TRUE
verbose	Ignored for now
...	Additional arguments passed on to plot or control functions
object	object of type tmle.SL.dbarts2
newdata	matrix or dataframe used to get predictions from the fitted model

Details

`tmle.SL.dbarts2` is in the default library for estimating Q . It uses the default setting in the `dbarts` package, $k = 2$. `tmle.SL.dbarts.k.5` is used to estimate the components of g . It sets $k = 0.5$, to avoid shrinking predicted values too far from $(0, 1)$. See `bart` documentation for more information.

Value

object an object of type `tmle.SL.dbarts2` used internally by Super Learner

Author(s)

Chris Kennedy and Susan Gruber

See Also

[SuperLearner](#)

tmleMSM

*Targeted Maximum Likelihood Estimation of Parameter of MSM***Description**

Targeted maximum likelihood estimation of the parameter of a marginal structural model (MSM) for binary point treatment effects. The `tmleMSM` function is minimally called with arguments (Y, A, W, MSM) , where Y is a continuous or binary outcome variable, A is a binary treatment variable, ($A=1$ for treatment, $A=0$ for control), and W is a matrix or dataframe of baseline covariates. MSM is a valid regression formula for regressing Y on any combination of A, V, W, T , where V defines strata and T represents the time at which repeated measures on subjects are made. Missingness in the outcome is accounted for in the estimation procedure if missingness indicator `Delta` is 0 for some observations. Repeated measures can be identified using the `id` argument.

Usage

```
tmleMSM(Y, A, W, V, T = rep(1, length(Y)), Delta = rep(1, length(Y)), MSM,
        v = NULL, Q = NULL, Qform = NULL, Qbounds = c(-Inf, Inf),
        Q.SL.library = c("SL.glm", "tmle.SL.dbarts2", "SL.glmnet"),
        cvQinit = TRUE, hAV = NULL, hAVform = NULL, g1W = NULL,
        gform = NULL, pDelta1 = NULL, g.Deltaform = NULL,
        g.SL.library = c("SL.glm", "tmle.SL.dbarts.k.5", "SL.gam"),
        ub = 1/0.025, family = "gaussian", fluctuation = "logistic",
        alpha = 0.995, id = 1:length(Y), V_SL = 5, inference = TRUE,
        verbose = FALSE, Q.discreteSL = FALSE, g.discreteSL = FALSE)
```

Arguments

<code>Y</code>	continuous or binary outcome variable
<code>A</code>	binary treatment indicator, 1 - treatment, 0 - control
<code>W</code>	vector, matrix, or dataframe containing baseline covariates. Factors are not currently allowed.
<code>V</code>	vector, matrix, or dataframe of covariates used to define strata
<code>T</code>	optional time for repeated measures data
<code>Delta</code>	indicator of missing outcome or treatment assignment. 1 - observed, 0 - missing
<code>MSM</code>	MSM of interest, specified as valid right hand side of a regression formula (see examples)
<code>v</code>	optional value defining the strata of interest ($V = v$) for stratified estimation of MSM parameter
<code>Q</code>	optional $n \times 2$ matrix of initial values for Q portion of the likelihood, $(E(Y A = 0, W), E(Y A = 1, W))$
<code>Qform</code>	optional regression formula for estimation of $E(Y A, W)$, suitable for call to <code>glm</code>
<code>Qbounds</code>	vector of upper and lower bounds on Y and predicted values for initial Q

Q.SL.library	optional vector of prediction algorithms to use for SuperLearner estimation of initial Q
cvQinit	logical, if TRUE, estimates cross-validated predicted values using discrete super learning, default=TRUE
hAV	optional $n \times 2$ matrix used in numerator of weights for updating covariate and the influence curve. If unspecified, defaults to conditional probabilities $P(A = 1 V)$ or $P(A = 1 T)$, for repeated measures data. For unstabilized weights, pass in an $n \times 2$ matrix of all 1s
hAVform	optional regression formula of the form $A \sim V + T$, if specified this overrides the call to SuperLearner
g1W	optional vector of conditional treatment assignment probabilities, $P(A = 1 W)$
gform	optional regression formula of the form $A \sim W$, if specified this overrides the call to SuperLearner
pDelta1	optional $n \times 2$ matrix of conditional probabilities for missingness mechanism, $P(Delta = 1 A = 0, V, W, T)$, $P(Delta = 1 A = 1, V, W, T)$.
g.Deltaform	optional regression formula of the form $Delta \sim A + W$, if specified this overrides the call to SuperLearner
g.SL.library	optional vector of prediction algorithms to use for SuperLearner estimation of g1W or pDelta1
ub	upper bound on observation weights. See Details section for more information
family	family specification for working regression models, generally 'gaussian' for continuous outcomes (default), 'binomial' for binary outcomes
fluctuation	'logistic' (default), or 'linear'
alpha	used to keep predicted initial values bounded away from (0,1) for logistic fluctuation
id	optional subject identifier
V_SL	number of cross-validation folds for Super Learner estimation of Q and g
inference	if TRUE, variance-covariance matrix, standard errors, pvalues, and 95% confidence intervals are calculated. Setting to FALSE saves a little time when bootstrapping.
verbose	status messages printed if set to TRUE (default=FALSE)
Q.discreteSL	If true, use discrete SL to estimate Q, otherwise ensembleSL by default. Ignored when SL is not used.
g.discreteSL	If true, use discrete SL to estimate components of g, otherwise ensembleSL by default. Ignored when SL is not used.

Details

ub bounds the IC by bounding the factor $h(A, V)/[g(A, V, W)P(Delta = 1|A, V, W)]$ between 0 and ub, default value = 1/0.025.

Value

psi	MSM parameter estimate
sigma	variance covariance matrix
se	standard errors extracted from sigma
pvalue	two-sided p-value
lb	lower bound on 95% confidence interval
ub	upper bound on 95% confidence interval
epsilon	fitted value of epsilon used to target initial Q
psi.Qinit	MSM parameter estimate based on untargeted initial Q
Qstar	targeted estimate of Q, an $n \times 2$ matrix with predicted values for $Q(\theta, W)$, $Q(1, W)$ using the updated fit
Qinit	initial estimate of Q. <code>Qinit\$coef</code> are the coefficients for a <code>glm</code> model for Q, if applicable. <code>Qinit\$Q</code> is an $n \times 2$ matrix, where n is the number of observations. Columns contain predicted values for $Q(\theta, W)$, $Q(1, W)$ using the initial fit. <code>Qinit\$type</code> is method for estimating Q
g	treatment mechanism estimate. A list with three items: <code>g\$g1W</code> contains estimates of $P(A = 1 W)$ for each observation, <code>g\$coef</code> the coefficients for the model for g when <code>glm</code> used, <code>g\$type</code> estimation procedure
g.AV	estimate for $h(A, V)$ or $h(A, T)$. A list with three items: <code>g.AV\$g1W</code> an $n \times 2$ matrix containing values of $P(A = 0 V, T)$, $P(A = 1 V, T)$ for each observation, <code>g.AV\$coef</code> the coefficients for the model for g when <code>glm</code> used, <code>g.AV\$type</code> estimation procedure
g_Delta	missingness mechanism estimate. A list with three items: <code>g_Delta\$g1W</code> an $n \times 2$ matrix containing values of $P(Delta = 1 A, V, W, T)$ for each observation, <code>g_Delta\$coef</code> the coefficients for the model for g when <code>glm</code> used, <code>g_Delta\$type</code> estimation procedure

Author(s)

Susan Gruber <sgruber@cal.berkeley.edu>, in collaboration with Mark van der Laan.

References

1. Gruber, S. and van der Laan, M.J. (2012), tmle: An R Package for Targeted Maximum Likelihood Estimation. *Journal of Statistical Software*, 51(13), 1-35. <http://www.jstatsoft.org/v51/i13/>
2. Rosenblum, M. and van der Laan, M.J. (2010), Targeted Maximum Likelihood Estimation of the Parameter of a Marginal Structural Model. *The International Journal of Biostatistics*, 6(2), 2010.

See Also

[summary.tmleMSM](#), [estimateQ](#), [estimateG](#), [calcSigma](#), [tmle](#)

Examples

```

library(tmle)
# Example 1. Estimating MSM parameter with correctly specified regression formulas
# MSM:  $\psi_0 + \psi_1*A + \psi_2*V + \psi_3*A*V$  (saturated)
# true parameter value:  $\psi = (0, 1, -2, 0.5)$ 
# generate data
set.seed(100)
n <- 1000
W <- matrix(rnorm(n*3), ncol = 3)
colnames(W) <- c("W1", "W2", "W3")
V <- rbinom(n, 1, 0.5)
A <- rbinom(n, 1, 0.5)
Y <- rbinom(n, 1, plogis(A - 2*V + 0.5*A*V))
result.ex1 <- tmleMSM(Y, A, W, V, MSM = "A*V", Qform = Y~., gform = A~1,
                    hAVform = A~1, family = "binomial")
print(result.ex1)
## Not run:
# Example 2. Repeated measures data, two observations per id
# (e.g., crossover study design)
# MSM:  $\psi_0 + \psi_1*A + \psi_2*V + \psi_3*V^2 + \psi_4*T$ 
# true parameter value:  $\psi = (-2, 1, 0, -2, 0)$ 
# generate data in wide format (id, W1, Y(t), W2(t), V(t), A(t))
set.seed(10)
n <- 250
id <- rep(1:n)
W1 <- rbinom(n, 1, 0.5)
W2.1 <- rnorm(n)
W2.2 <- rnorm(n)
V.1 <- rnorm(n)
V.2 <- rnorm(n)
A.1 <- rbinom(n, 1, plogis(0.5 + 0.3 * W2.1))
A.2 <- 1-A.1
Y.1 <- -2 + A.1 - 2*V.1^2 + W2.1 + rnorm(n)
Y.2 <- -2 + A.2 - 2*V.2^2 + W2.2 + rnorm(n)
d <- data.frame(id, W1, W2=W2.1, W2.2, V=V.1, V.2, A=A.1, A.2, Y=Y.1, Y.2)

# change dataset from wide to long format
longd <- reshape(d,
                varying = cbind(c(3, 5, 7, 9), c(4, 6, 8, 10)),
                idvar = "id",
                direction = "long",
                timevar = "T",
                new.row.names = NULL,
                sep = "")
# misspecified model for initial Q, partial misspecification for g.
# V_SL set to 2 to save time, not recommended at this sample size
result.ex2 <- tmleMSM(Y = longd$Y, A = longd$A, W = longd[,c("W1", "W2")], V = longd$V,
                    T = longd$T, MSM = "A + V + I(V^2) + T", Qform = Y ~ A + V, gform = A ~ W2,
                    id = longd$id, V_SL=2)
print(result.ex2)

```

```
# Example 3: Introduce 20
# V_SL set to 2 to save time, not recommended at this sample size
Delta <- rbinom(nrow(longd), 1, 0.8)
result.ex3 <- tmleMSM(Y = longd$Y, A = longd$A, W = longd[,c("W1", "W2")], V = longd$V, T=longd$T,
  Delta = Delta, MSM = "A + V + I(V^2) + T", Qform = Y ~ A + V, gform = A ~ W2,
  g.Deltaform = Delta~ 1, id=longd$id, verbose = TRUE, V_SL=2)
print(result.ex3)

## End(Not run)
```

tmleNews

Show the NEWS file (tmleNews)

Description

Shows recent changes and bug fixes documented in the tmle package NEWS file.

Usage

```
tmleNews(...)
```

Arguments

... additional arguments passed to RShowDoc

Value

NONE

Author(s)

Susan Gruber

See Also

[tmle](#), [tmleMSM](#)

Index

*Topic **datasets**

fev, 8

calcParameters, 3, 7, 8, 17

calcSigma, 4, 4, 7, 8, 17, 22

estimateG, 4, 5, 6, 8, 17, 22

estimateQ, 4, 5, 7, 7, 17, 22

fev, 8

methods, 10, 12

oneStepATT, 9, 17

predict.tmle.SL.dbarts2

(tmle.SL.dbarts2), 18

print.summary.tmle(summary.tmle), 10

print.summary.tmleMSM

(summary.tmleMSM), 12

print.tmle(summary.tmle), 10

print.tmleMSM(summary.tmleMSM), 12

summary.tmle, 10, 17

summary.tmleMSM, 12, 22

SuperLearner, 19

tmle, 3–5, 7–9, 11, 13, 22, 24

tmle-package, 2

tmle.SL.dbarts.k.5(tmle.SL.dbarts2), 18

tmle.SL.dbarts2, 18

tmleMSM, 3–5, 7, 8, 13, 17, 20, 24

tmleNews, 24