

IMP — A WHILE-language and two semantics

Heiko Loetzbeyer and Robert Sandner

June 21, 2010

Abstract

The formalization of the denotational and operational semantics of a simple while-language together with an equivalence proof between the two semantics. The whole development essentially formalizes/transcribes chapters 2 and 5 of [1]. A much extended version of this development is found in HOL/IMP of the Isabelle distribution.

Contents

1	Arithmetic expressions, boolean expressions, commands	1
1.1	Arithmetic expressions	1
1.2	Boolean expressions	2
1.3	Commands	3
1.4	Misc lemmas	4
2	Denotational semantics of expressions and commands	4
2.1	Definitions	4
2.2	Misc lemmas	5
3	Equivalence	5
3.1	Main theorem	6

1 Arithmetic expressions, boolean expressions, commands

theory Com imports Main begin

1.1 Arithmetic expressions

consts

loc :: i

aexp :: i

datatype \subseteq "univ(loc \cup (nat \rightarrow nat) \cup ((nat \times nat) \rightarrow nat))"

aexp = N ("n \in nat")

```

| X ("x ∈ loc")
| Op1 ("f ∈ nat -> nat", "a ∈ aexp")
| Op2 ("f ∈ (nat × nat) -> nat", "a0 ∈ aexp", "a1 ∈ aexp")

consts evala :: i

abbreviation
  evala_syntax :: "[i, i] => o"      (infixl "-a->" 50)
  where "p -a-> n == <p,n> ∈ evala"

inductive
  domains "evala" ⊆ "(aexp × (loc -> nat)) × nat"
  intros
    N: "[| n ∈ nat; sigma ∈ loc->nat |] ==> <N(n),sigma> -a-> n"
    X: "[| x ∈ loc; sigma ∈ loc->nat |] ==> <X(x),sigma> -a-> sigma'x"
    Op1: "[| <e,sigma> -a-> n; f ∈ nat -> nat |] ==> <Op1(f,e),sigma> -a-> f'n"
    Op2: "[| <e0,sigma> -a-> n0; <e1,sigma> -a-> n1; f ∈ (nat×nat) -> nat |]
          ==> <Op2(f,e0,e1),sigma> -a-> f'<n0,n1>"
  type_intros aexp.intros apply_funtype

```

1.2 Boolean expressions

```

consts bexp :: i

datatype ⊆ "univ(aexp ∪ ((nat × nat)->bool))"
  bexp = true
        | false
        | ROp ("f ∈ (nat × nat)->bool", "a0 ∈ aexp", "a1 ∈ aexp")
        | noti ("b ∈ bexp")
        | andi ("b0 ∈ bexp", "b1 ∈ bexp")      (infixl "andi" 60)
        | ori ("b0 ∈ bexp", "b1 ∈ bexp")      (infixl "ori" 60)

consts evalb :: i

abbreviation
  evalb_syntax :: "[i,i] => o"      (infixl "-b->" 50)
  where "p -b-> b == <p,b> ∈ evalb"

inductive
  domains "evalb" ⊆ "(bexp × (loc -> nat)) × bool"
  intros
    true: "[| sigma ∈ loc -> nat |] ==> <true,sigma> -b-> 1"
    false: "[| sigma ∈ loc -> nat |] ==> <false,sigma> -b-> 0"
    ROp: "[| <a0,sigma> -a-> n0; <a1,sigma> -a-> n1; f ∈ (nat*nat)->bool |]
          ==> <ROp(f,a0,a1),sigma> -b-> f'<n0,n1> "
    noti: "[| <b,sigma> -b-> w |] ==> <noti(b),sigma> -b-> not(w)"
    andi: "[| <b0,sigma> -b-> w0; <b1,sigma> -b-> w1 |]
          ==> <b0 andi b1,sigma> -b-> (w0 and w1)"

```

```

ori:    "[| <b0,sigma> -b-> w0; <b1,sigma> -b-> w1 |]"
        ==> <b0 ori b1,sigma> -b-> (w0 or w1)"
type_intros  bexp.intros
            apply_funtype and_type or_type bool_1I bool_0I not_type
type_elims   evala.dom_subset [THEN subsetD, elim_format]

```

1.3 Commands

```

consts com :: i
datatype com =
  skip                                ("skip" [])
  | assignment ("x ∈ loc", "a ∈ aexp") (infixl "⊢=" 60)
  | semicolon ("c0 ∈ com", "c1 ∈ com") ("_;_" [60, 60] 10)
  | while ("b ∈ bexp", "c ∈ com") ("while _ do _" 60)
  | if ("b ∈ bexp", "c0 ∈ com", "c1 ∈ com") ("if _ then _ else _" 60)

```

```

consts evalc :: i

```

```

abbreviation
  evalc_syntax :: "[i, i] => o" (infixl "-c->" 50)
  where "p -c-> s == <p,s> ∈ evalc"

```

inductive

```

domains "evalc" ⊆ "(com × (loc -> nat)) × (loc -> nat)"

```

intros

```

skip:    "[| sigma ∈ loc -> nat |] ==> <skip,sigma> -c-> sigma"

```

```

assign:  "[| m ∈ nat; x ∈ loc; <a,sigma> -a-> m |]"
        ==> <x := a,sigma> -c-> sigma(x:=m)"

```

```

semi:    "[| <c0,sigma> -c-> sigma2; <c1,sigma2> -c-> sigma1 |]"
        ==> <c0; c1, sigma> -c-> sigma1"

```

```

if1:     "[| b ∈ bexp; c1 ∈ com; sigma ∈ loc->nat;
            <b,sigma> -b-> 1; <c0,sigma> -c-> sigma1 |]"
        ==> <if b then c0 else c1, sigma> -c-> sigma1"

```

```

if0:     "[| b ∈ bexp; c0 ∈ com; sigma ∈ loc->nat;
            <b,sigma> -b-> 0; <c1,sigma> -c-> sigma1 |]"
        ==> <if b then c0 else c1, sigma> -c-> sigma1"

```

```

while0:  "[| c ∈ com; <b, sigma> -b-> 0 |]"
        ==> <while b do c,sigma> -c-> sigma"

```

```

while1:  "[| c ∈ com; <b,sigma> -b-> 1; <c,sigma> -c-> sigma2;
            <while b do c, sigma2> -c-> sigma1 |]"
        ==> <while b do c, sigma> -c-> sigma1"

```

```

type_intros  com.intros update_type

```

```

type_elims   evala.dom_subset [THEN subsetD, elim_format]
              evalb.dom_subset [THEN subsetD, elim_format]

```

1.4 Misc lemmas

```

lemmas evala_1 [simp] = evala.dom_subset [THEN subsetD, THEN SigmaD1, THEN SigmaD1]
  and evala_2 [simp] = evala.dom_subset [THEN subsetD, THEN SigmaD1, THEN SigmaD2]
  and evala_3 [simp] = evala.dom_subset [THEN subsetD, THEN SigmaD2]

```

```

lemmas evalb_1 [simp] = evalb.dom_subset [THEN subsetD, THEN SigmaD1, THEN SigmaD1]
  and evalb_2 [simp] = evalb.dom_subset [THEN subsetD, THEN SigmaD1, THEN SigmaD2]
  and evalb_3 [simp] = evalb.dom_subset [THEN subsetD, THEN SigmaD2]

```

```

lemmas evalc_1 [simp] = evalc.dom_subset [THEN subsetD, THEN SigmaD1, THEN SigmaD1]
  and evalc_2 [simp] = evalc.dom_subset [THEN subsetD, THEN SigmaD1, THEN SigmaD2]
  and evalc_3 [simp] = evalc.dom_subset [THEN subsetD, THEN SigmaD2]

```

```

inductive_cases
  evala_N_E [elim!]: "<N(n),sigma> -a-> i"
  and evala_X_E [elim!]: "<X(x),sigma> -a-> i"
  and evala_Op1_E [elim!]: "<Op1(f,e),sigma> -a-> i"
  and evala_Op2_E [elim!]: "<Op2(f,a1,a2),sigma> -a-> i"

```

end

2 Denotational semantics of expressions and commands

theory Denotation imports Com begin

2.1 Definitions

consts

```

A      :: "i => i => i"
B      :: "i => i => i"
C      :: "i => i"

```

definition

```

Gamma :: "[i,i,i] => i" ("Γ") where
  "Γ(b,cden) ==
    (λphi. {io ∈ (phi 0 cden). B(b,fst(io))=1} ∪
      {io ∈ id(loc->nat). B(b,fst(io))=0})"

```

primrec

```

"A(N(n), sigma) = n"
"A(X(x), sigma) = sigma`x"
"A(Op1(f,a), sigma) = f`A(a,sigma)"
"A(Op2(f,a0,a1), sigma) = f`<A(a0,sigma),A(a1,sigma)>"

```

primrec

```
"B(true, sigma) = 1"
"B(false, sigma) = 0"
"B(ROp(f,a0,a1), sigma) = f'<A(a0,sigma),A(a1,sigma)>"
"B(noti(b), sigma) = not(B(b,sigma))"
"B(b0 andi b1, sigma) = B(b0,sigma) and B(b1,sigma)"
"B(b0 ori b1, sigma) = B(b0,sigma) or B(b1,sigma)"
```

primrec

```
"C(skip) = id(loc->nat)"
"C(x := a) =
  {io ∈ (loc->nat) × (loc->nat). snd(io) = fst(io)(x := A(a,fst(io)))}"
"C(c0; c1) = C(c1) ∪ C(c0)"
"C(if b then c0 else c1) =
  {io ∈ C(c0). B(b,fst(io)) = 1} ∪ {io ∈ C(c1). B(b,fst(io)) = 0}"
"C(while b do c) = lfp((loc->nat) × (loc->nat), Γ(b,C(c)))"
```

2.2 Misc lemmas

lemma *A_type* [TC]: "[|a ∈ aexp; sigma ∈ loc->nat|] ==> A(a,sigma) ∈ nat"
 <proof>

lemma *B_type* [TC]: "[|b ∈ bexp; sigma ∈ loc->nat|] ==> B(b,sigma) ∈ bool"
 <proof>

lemma *C_subset*: "c ∈ com ==> C(c) ⊆ (loc->nat) × (loc->nat)"
 <proof>

lemma *C_type_D* [dest]:
 "[| <x,y> ∈ C(c); c ∈ com |] ==> x ∈ loc->nat & y ∈ loc->nat"
 <proof>

lemma *C_type_fst* [dest]: "[| x ∈ C(c); c ∈ com |] ==> fst(x) ∈ loc->nat"
 <proof>

lemma *Gamma_bnd_mono*:
 "cden ⊆ (loc->nat) × (loc->nat)
 ==> bnd_mono ((loc->nat) × (loc->nat), Γ(b,cden))"
 <proof>

end

3 Equivalence

theory *Equiv* imports *Denotation* *Com* **begin**

lemma *aexp_iff* [rule_format]:
 "[| a ∈ aexp; sigma: loc -> nat |]"

```

    ==> ALL n. <a,sigma> -a-> n <-> A(a,sigma) = n"
  <proof>

declare aexp_iff [THEN iffD1, simp]
        aexp_iff [THEN iffD2, intro!]

inductive_cases [elim!]:
  "<true,sigma> -b-> x"
  "<false,sigma> -b-> x"
  "<ROp(f,a0,a1),sigma> -b-> x"
  "<noti(b),sigma> -b-> x"
  "<b0 andi b1,sigma> -b-> x"
  "<b0 ori b1,sigma> -b-> x"

lemma bexp_iff [rule_format]:
  "[| b ∈ bexp; sigma: loc -> nat |]
   ==> ALL w. <b,sigma> -b-> w <-> B(b,sigma) = w"
  <proof>

declare bexp_iff [THEN iffD1, simp]
        bexp_iff [THEN iffD2, intro!]

lemma com1: "<c,sigma> -c-> sigma' ==> <sigma,sigma'> ∈ C(c)"
  <proof>

declare B_type [intro!] A_type [intro!]
declare evalc.intros [intro]

lemma com2 [rule_format]: "c ∈ com ==> ∀ x ∈ C(c). <c,fst(x)> -c-> snd(x)"
  <proof>

3.1 Main theorem

theorem com_equivalence:
  "c ∈ com ==> C(c) = {io ∈ (loc->nat) × (loc->nat). <c,fst(io)> -c-> snd(io)}"
  <proof>

end

```

References

- [1] Glynn Winskel. *The Formal Semantics of Programming Languages*. 1993.