########

<ale@FreeBSD.org>
########: 43126

####### ## # ########## ######### ## ### ####### ##########.

3### ### ########### ### ########## ########## ## 3### ###–
########.

#####, #######, ############, #386, #486, #######, #######, ###
###–
######## ## ### ############ ## ### ###### ###### ### #####
#########.

##
########### ##### ######## ### ####### ## ##########. #####
########, ### ###
####### ### ##### ## ### ######### #####, ### ############
######.

2013#11#07 ## #####.

########

(####
########) #### ### ######## ######## ####### ###### ## ###–
#######, ### ### # ###### ## #### #### ########. ###
######.
##–
######.

(#####–
#########) ## ### ####### ######### ## #### ## ###
########## ### #### ########## ### ####### ####### ### ###
######## #### ## ### ###### ### ### ########### ### ## ###–
########. ##### #### ###### ## #### # ###### ##
#####.

########

1. ### ### # ######### ######? 2
2. ### ## ####### 2
3. ##### ########### 3

4. ######## ### ###### 4
5. ########### ### ######## 5
6. ############ 8

1. ### ### # ######### ######?

##########, ###### ## ### ######## ##### ## ##### #### ######## ########### (####) ### #### ####### ## ### ######### ## ######### ###4 #######–##, #### ######### ### ######### ## ### ######## 24 ##### ## 24 ### #### ### (######### ### #### # ##### ## 2) ## #########. ## ##### ########## ## ## ##### ######### ## #### # ######## #### ####### ######## ### ######## ####### #### ### ####### ########, ### # ###### ######### ######## ##### ## ###### ### ### ## ##########, ###### ### ## ########## ######, ### ###### ## ##### ## ### ######–###### ######## (###), ## ####### ## #### ### ####### #### ###############. ## ##### ######### ### ### ## # ######### ###### ## ###### #######.

###/###### ####### ### ## ######### ######.

2. ### ##

#########. ##### 4.5 ####### ## ## ######## ## #### #### ############### ## ####### ####### ## ###### ## ####### ### ######, ########### ### ######### # ##### ####. ## ### ######### ########### # #### ####### #### ############ ####.

#########

Do not ###### #### ############: # ######### *excludes* ### ##### ###. ###### ### #### ###### ######### ## #### ##### ### #########.

##, ## #### ## #### ## ##### ### ######## ##### #### ####### ### ########### #### ### #### ######### ### ############, ##### #### #### ## #### ## #### ######## ####### #### ### #######, ### #### ##### ###. ########, ## #### # #### ##########, ### ##### ###### ## ### ### ######### #####. ### #### ####### ### ##### ### ##### ############™ ###, ######## ## ### 3###® 3#9## ######. ## ######## ### ######## ############# ## ### ## ###### ## #### ### ##### ## ###–###### ############# (##### ######### #######) ## ##### ## ########### ####### ##### ######### ## ######### ## ### ###### ### ##### ## ### ##### #######.

2.1. ######

######. ## #####, ### #### ## ### ### ######### #### ## #### ###### ############# ####:

```
options BRIDGE
options IPFIREWALL
options IPFIREWALL_VERBOSE
```

#######, ### ###### ### ## ### ######## ### ### ##### ### ## ### ####### ######### ## ### ########.

######. ### ### #### ######## ##–########## ## ### ######## ### ########## # ###### ###### ####### ## ### ####–### ########.

2.2. #######

######, ### #### ##### ## ## ### ## ### ### ######### ### ## /boot/loader.conf:

```
bridge_load="YES"
```

###, ###### ### ###### #######, ### bridge.ko ###### #### ## ###### ######## #### ### ######. ## ## ### ######## ## ### # ####### ### ### ### ipfw.ko ######, ##### ## #### ## ###### ############# ##### ### ######### ## ### ##### ## ### ######### #######.

3. #####

(##–####### ## ### ########## ###### ############ ######), ### #### ## #### #### ####### ## ### /etc/rc.conf ############# ####. ### ####### #### ## ### ######## ## ## ###### ### ## #######. ######### ## #### ### ## ## open ########, ## ##### ## ###### ### ######### ####### ### ##### ####### ## ###### ######### (## #### ### ### ##### ## ####### #### ######### ########, #### ############# #### ##### ### ## ###### ######## #### ### #######). ### ##### ##### ## /etc/rc.conf:

```
firewall_enable="YES"
firewall_type="open"
firewall_quiet="YES"
firewall_logging="YES"
```

(### #### #### ### ###### ipfw.ko ## ## ## ### ######## ## ### ######), ### ###### ### ## ### ## ## ## open #### (## ######### ## /etc/rc.firewall), ### ##### ### ## ### #### ##### ####### ### ### ###### ### ## ###### ####### #######.

##########, ### #### #### ### ## ## ###### ## ## ## #### ### ## ### ####### #####, ### ### ###### #### #### ####### #### ## #### ########## ## #### ### # ########## ##. ## ### #### #### (#######) ### ###### ####### #### ## ##### #### ######, ## ############ #### ### #######: ## ######### ##, ### #### ## ##### #### ####### ## ####### # ##### ####### ######### ######### #### ### ######. #########, ###### ### ###### #######, #### ######## ####### ####### ######, ### ### ###### ##########: ## #### #### ## ## ######### ## ###### ## ## ## ### ######## ######### (### ### ######### ## ########, ##### ### ###### #######), ##### ### ###### #### ## ######### ## ### ### ## ### ####### #########. ## ##### #### ### fxp0 ######### (## ### ####) #### ## ######### ## ### ######## ####### ## ### /etc/rc.conf ####, ##### ### xl0 ## ###. ######### ## ## ## #### ### ####### ##### #### ### #### #### #####, ######, ###### ### ##### #########, ############ ###### ###### ## ######## ## #### ######## ########.

####. #### ####### ## #### ########, ##### ### ######## ### ######## ######### ## ###: ### ## ##, ### ##### ## ###. ### #### ### ########## ## ### ## ####### ## # #### #### ### ######## ####### (### #####). ## ##### ## ##### ### ############# ####### ### ##### ######### ## ### ######, ## ## ######### #### ### ###### #### ####### ### #######. #### ######## ## ### ######## ## ### ## #####, ##### ## ###### #### #### ## #### ########. ### ####### ######## ####### ########### ## ### ## ##### ### ######### ### ###### ####### (### ########) #### ## ######### ####### ##### ########, #### ## ### ######## ## ########## ## ### ###### ########.

######: ##### #### ## #### ### ######## ##### ### ###### ### ### ########, ### ### ###### #### ### ## ######### ### ### ########, ##### ## open ####, #### ### ##### ### ##########.

########, ### ###### #### #### ### ### ###### ##########.

4. ######## ###

#####, ## ###### ### ######, ### #### ## ####### ### ######### ######## (###### ### ########## ## ####### ### ##### ## ### ### ####### ########## fxp0 ### xl0 #### #### ### ####):

```
# sysctl net.link.ether.bridge.config=fxp0:0,xl0:0
# sysctl net.link.ether.bridge.ipfw=1
# sysctl net.link.ether.bridge.enable=1
```

######, ### ###### ### #### ###### ### ######## ## ### ###### ### ####### ### ##### ### #### ###### ### ######.

> ####
>
> ## ### #### ####### 5.1######## ## ######## ### ###### ####–##### ### ####### ###########. ### ######(4) ### #######.

####. ## ##, ### #### #### ## ## ### ### net.link.ether.bridge.[blah]=[blah] ######## ## ##### #### ## ### /etc/sysctl.conf ####, ## ##### ## #### #### ####### ## #######.

5. ########### ###

#####, ## ##### ## ###### ### ###### #######. ##### #### ## #### ############ ## ##### #### ####### ### ### ## ### ######## ############### ### ######### ## ####### #######. ###–########, ##### ## # ########## ####### ### ####### #### ### ## ### ####### ## ##### ######### ### ####### #### ### ##### ######## ## ### ##### #######. ## #######, ######## ####### ### ### ####### ### ######## #### ####, ### ##### ## ## ######## ### ####; ## #### #### ### ######## #### #### #######, ## ##### #### ### out ## xmit #### ##### #####. ##########, # ### in via ##### ## ## ##### ######, ### ### #### ### # ##### #### ### #### ##. ####### ########## ## #### ### ### ########## ## ### #### pass ## drop ######## ### ####### ######## ## # ######. ############## ###### #### divert, forward ## reject ### ### #########. #### ####### ### ##### ## ####, ### #### ## ####### ## ## #### ### ###### ####### ###### (## ## ### ## ## #######).

4.0, ## ### ####### ## ######## #########. #### ## # ### #######–#### ### ### #######, ##### ######### ## # ####### ##### ###, ######## ####### ########## ## # ######## #### ### ##### #### ### ## ## ######### ### #### ####### (### #### ###### ### ########### ########, ## ######). ### ######### #### #### ## ############, ##### ## ###### ## ### ## #### #### #### #### ## ####### ## # ###### #######. ### #### # ######## #### ### ########## ## ######## ### ###### ###, ### ### #### ### #######, ##### # ########, ######## ### ######## ## #######. ### ######### ####### ##### ### ## ## ##. ## ## ######## ## ## ### #### ##### #### ### #######. #### ###### ### ## ##### #### ###### ## ####### ####### ### ##### ##### ######, ### ## #### ######### ##### #### ##### ##### #### ####### ## ####.

#####. #### ##### #### ## ### ### ## /etc/rc.firewall ##### ### ####### ######## ##### ### ### ######## ######### lo0, ## ## ###### ### #### ## #### ### #### #######. ###### ##### ###### ## ### ## # ######## #### (### /etc/

rc.firewall.local) ### ###### ## ###### #######, ## ######### ### ### ## /etc/rc.conf ##### ## ####### ### open ########:

```
firewall_type="/etc/rc.firewall.local"
```

full ####, ######### ## #### ### ## ###### #### ### #### ## ###### ######## #### ### #######.

fxp0 ######### ######### ####### ### ####### (########) ### ### xl0 ####### ### ###### (###). ### ###### ####### ### ### ## 1.2.3.4 (## ## ### ######## #### #### ### ### #### ### ## ####### ##### #### ####, ### ### ### ####### ## ## ####).

```
# Things that we have kept state on before get to go through in a hurry
add check-state

# Throw away RFC 1918 networks
add drop all from 10.0.0.0/8 to any in via fxp0
add drop all from 172.16.0.0/12 to any in via fxp0
add drop all from 192.168.0.0/16 to any in via fxp0

# Allow the bridge machine to say anything it wants
# (if the machine is IP-less do not include these rows)
add pass tcp from 1.2.3.4 to any setup keep-state
add pass udp from 1.2.3.4 to any keep-state
add pass ip from 1.2.3.4 to any

# Allow the inside hosts to say anything they want
add pass tcp from any to any in via xl0 setup keep-state
add pass udp from any to any in via xl0 keep-state
add pass ip from any to any in via xl0

# TCP section
# Allow SSH
add pass tcp from any to any 22 in via fxp0 setup keep-state
# Allow SMTP only towards the mail server
add pass tcp from any to relay 25 in via fxp0 setup keep-state
# Allow zone transfers only by the slave name server [dns2.nic.it]
add pass tcp from 193.205.245.8 to ns 53 in via fxp0 setup keep-state
# Pass ident probes.  It is better than waiting for them to timeout
add pass tcp from any to any 113 in via fxp0 setup keep-state
# Pass the -"quarantine" range
add pass tcp from any to any 49152-65535 in via fxp0 setup keep-state

# UDP section
# Allow DNS only towards the name server
```

```
add pass udp from any to ns 53 in via fxp0 keep-state
# Pass the -"quarantine" range
add pass udp from any to any 49152-65535 in via fxp0 keep-state

# ICMP section
# Pass -'ping'
add pass icmp from any to any icmptypes 8 keep-state
# Pass error messages generated by -'traceroute'
add pass icmp from any to any icmptypes 3
add pass icmp from any to any icmptypes 11

# Everything else is suspect
add drop log all from any to any
```

#######. ## ##########, ##### ### ## ############# #####, ## #### ## ### *not* ###:

```
add deny all from 1.2.3.4/8 to any in via fxp0
```

##, #### ####### #### ### ###### ## #### ### ####### ######## ## ## #### ### #######. #### ## ######### #### ### ##### ######## ## ## ## #### #### ####### #### ### ### ## ##### ### ###### ######, ## ########## ######### ####### #### #### #### #### ### #### ### ######. ### ####### #### #### ## #### ##### ## *at least* ### #### ## ### ####### ######### #### ### ## ### #### ## ######: ### ######. ### #######, ### ### ########### ## ##### ######, ## ## ## ### #### ## ###### #### ####.

####, #### ##, ## ### ### ######## #### #### ## ### ############ #######. ### ##### ## # ##########: ### ######### ####### #### ## ######.

######, ## ### #### ####. ######### ### ##### #### ### ###### ## ######## ## ######## #####, #### ## #### # ######## ####### (#### ###### ## ######### ##–######## ## ### ####(8) ### ####). #### #### ## ##### ### ####### ### #### ## ####, #### ####### ####### #### #### *before* ### ###### ## #######. #### ## ## ####### ## ###### #### #### ### ### ### ## ## ### ####### ####### ####. ############# ## ## ######## ## ####### ### ## ####### ####### ## ### #### #### (######## ## ### ####### ## #######).

reset ## # forward #### ### ##### ####### (### #### 113). #############, #### ## ### ## ########## ###### #### ### ######, ## ### #### ##### ## ## ###### #### #### ## ##### ###########. ## #### ## #### ########### ####### ## ### ####### ## ##### ######, #### ## ########## ########. ### ########### ## ######## ######–##### ## #### 113, ##### ####### #### ######## #### ######## #### ### (### ##### ##### #### #######).

#####, ### ####### ### ######## #####. ######## #### #### ## ####### ### ### #### ## ####### #### #### ######### ##### ####### ### ###### ### #### ### ###### ######. ### ###### ### #### ## ####### ### ######, ##### ### ##### ####### #### ### ### ###### ## ##### ## #####. #### ### ### ##### ## ###### ### ######### #####. ### in via fxp0 ##### #### ### #### #####. ## #######, ## ### ### in via ##### ########## ### ######, ### #### #### ## #### ## ######### ### ####### ######### #######, ####### #### ### ### #### ## ### ### ## ### ##########.

6.

#####, ####### ### ####### #### ## ### #### ##### ########, ###### ## #### #####. # #### ## ############ ### ### ## ## #####–####### ## ######## ## ##### ########.

#########.

(### ######## ######## ## #### #######) #### #######.