

#####

#####

#####: [43126](#)

© 2001, 2002, 2003

#####/##### #66001#01###8035 (# ##### #), ## #####
#####

#####

#####

Version française de Clément Mathieu <cykl@mAdchAt.org>.

#####

1. #####	2
2. #####	2
3. #####	6
4. #####	10
5. #####	13
6. #####	16
7. #####	16
8. #####	16
9. #####	20
10. #####	23
11. #####	26

#####

#####.

##—
##—
#####. ##

#####; ##### ## ##### ##

#####.

#####. #####
##, ## ##### ## #####, ##

#####.

#####.

##—

#####.

2.2.

#####.

2.2.1. ##### ##

alice ##### **##(1)** ##### root.

```
% whoami
alice
% ls -l `which su`
-r-sr-xr-x 1 root wheel 10744 Dec 6 19:06 /usr/bin/su
% su --
Password: xi3kiune
# whoami
root
```

- ## ##### ## alice.

- ## ##### ## root.
- ## ##### **##(1)** ## # ## ##### ## #####.
- ## ##### ##### ## xi3kiune.
- ##### ## root, ## ##### **##(1)** ## ##### root.

2.2.2. ##### ## ##### ##### #####.

```
##### eve ##### ### ##### ##(1) ###
login.example.com, ## ##### # ## ##### ## ##### bob. ## ##### #####. ##
##### # ##### # ##### ## # ##### !
```

```
% whoami
eve
% ssh bob@login.example.com
bob@login.example.com's password: god
Last login: Thu Oct 11 09:52:57 2001 from 192.168.0.1
Copyright (c) 1980, 1983, 1986, 1988, 1990, 1991, 1993, 1994
The Regents of the University of California. All rights reserved.
FreeBSD 4.4-STABLE (LOGIN) #4: Tue Nov 27 18:10:34 PST 2001

Welcome to FreeBSD!

%
```

- ## ##### ## eve.
- ## ##### ##eve ### ##### ## ## ##### ##(1)
- ## ##### ## ## ##### ##(8) ## login.example.com
- ## ##### ## bob.
- ## ##### ##### ## god.
- ##### ## ## ## ## ## ## ## ## ## ## ## ## ## ## root.

2.2.3. ##### ##

```
### ##### ### ##### ##### ### ##### ### ##### ## sshd:
```

```
sshd auth required pam_nologin.so no_warn
sshd auth required pam_unix.so no_warn try_first_pass
sshd account required pam_login_access.so
sshd account required pam_unix.so
sshd session required pam_lastlog.so no_fail
sshd password required pam_permit.so
```

#####

- ##### sshd (#####
(8))
- auth, account, session ## password #####.
- pam_nologin.so, pam_unix.so, pam_login_access.so, pam_lastlog.so ## pam_permit.so ##### ##
#####. ## ## ##### ##
pam_unix.so ##### ##
(#####).

2.3.

#####

3. #### ##### ## ####

3.1. ##### ##

```
#####  ###  #####  ###  #####  #####  #####  #####  #####  #####
#####  #####  #####  #####  #####  #####  #####  #####.
```

auth

Authentication. ## #####

#####.## ##### :

- **###_#####(3)** ##### ## #####, ##### ## #####
 ## ##### ##### ## ## ## ##### ## ## ##### ##### ##
 ##### ## ##### ## ##### ## ## ##### ##### #####.
- **###_#####(3)** ##### ## ##### ## ##### ## ## ## ##, ## ##
 ##### ## ##### ## ## ## ##### ## ## ##### ## ## #####.

account

Gestion de compte. ## ##### ## ##### ## ##### ## #####
#####. ## #####
#####. ## #####:

- ### #### ###(3) ##### ### ## ##### ##### ### #####.

session

Gestion de session. ## ##### ## ##### ## ##### ## ## ##### ## ##
#####, ## ##### ##### ## ## ##### ##### ## ## #####.
#####:

- `###_###_#####(3) ##### ## ##### ##### # ## ##### ## #####`
`##### : ##### ## ##### ##### ##### utmp ## wtmp, ##### ##`
`##### ##...`

3.3.

, ##
 #####_####(3). ##
 #####
 #####
 ##### : ##
 #####

 #####
 #####

:
 #####

binding

 #####
 #####

9
 (#### 5.9); #####

required

 #####
 #####

requisite

 #####
 #####

sufficient

 #####
 #####

 #####
 ##### binding #
 #####

#####

optional

#####. ## ##### ## ##### ## ##
optional, ##### ## ##### ##### #####.

##, ## ##### ## #####

#####, ##### ## ## ## ## ##### ## #####
(#### # ##### ## ##### ##
binding ## sufficient, #### # ##### ## ##### ## ##### requisite). ## ##### ##
#####, ## ## ## ##
#####.

#####, #### ## ## #####, ##### ## ##### ##### ##—
#####. ## ##### ## ##### ## ##### ## ## ##—

#####.

##.

3.4.

#####. ##### ##
##, ## ##### ##### ##### ## #####
#####.

1. ## #####, ## ##### ##### ## ##### ## ##
root
root.
2. ## ##### ## [###_####\(3\)](#) ## ##### ## ##### ## ##—
#####, ## ##### ## #####—
#####.
3. ## ##### ##### ##### ##### ## ##### (### ##

#####) ## ## ## ## ## ##### [###_###_####\(3\)](#).
4. ## ##### ## [###_#####\(3\)](#) ## #####.
5. ## ##### ## ##### [###_####_####\(3\)](#) ## ##### ## ##
#####. ## ## ## ## ## ## ## ##
####, [###_####_####\(3\)](#) ##### PAM_NEW_AUTHTOK_REQD # ## ##
PAM_SUCCESS.
6. ## ##### # ##### PAM_NEW_AUTHTOK_REQD, ## #####
[###_#####\(3\)](#) ## ##### # #####
#####.

###

7. ##### ##-##### # ##-#####
#####(3) ##### ##-#####
##-#####
#####.
8. ##### ##-#####
#####(3) #####.
9. ##### ##-#####
#####.
10. ##### ##-#####(3)
#####.
11. #####(3) #####

#####.

4. ##### ## ###

4.1. ##### ## #####

```
##### #/etc/pam.conf.#####
#####.#####
#####.,#####:
```

```
login auth required pam_nologin.so no_warn
```

```
##### #, #, # #, #  
#####, # # # # #. #####  
##### # # # #.
```

[illegible]

```
##### ## ##### ##### ## ##### ## ##### ##### ## ##
##### ##### ##### ## ##### ##### ##### ## ## ##
##### ## ##### ##### ## ##### ##### /etc/pam.d/ ## ##
##### ##### ## ##### ## ## ##### ##### ## ## #####
```

#####

####. ## ##### ## ##### ## ##### 4.##. ##### ## ## ## ##### /etc/
pam.conf ##### ## ##### ## ##### ## ##### ## ## #####
/etc/pam.d, ## ##### ## ##
#####.

/etc/pam.d/ ## /etc/pam.conf ## ##### ## ##### ##
##—
#####. ## ##### ## ##### ## ##### ## ##
su ## sudo, ## ##### ## ## ## :

```
# cd -/etc/pam.d  
# ln -s su sudo
```


#####, ##### ## ## ##—
#####.

##—
/etc/pam.conf. #####
#####, ##### ##### ## /usr/local/etc/pam.d #####
#####; ##### ## ##### ## ## ## ## ##
/etc/pam.d/ ## /etc/pam.conf.

#####, ##### ## ## ##### ## ## #####, ## ##### # ##—
other ## ##### ## ## ## ## ## ## ## ##
#####.

4.2. ##### ## #

4.1, # ##### ## ##### #,
pam.conf ##### ## ##### ## #####: ## ## ## ##
#####, ## ##### ## #####, ## ## ## ## ##
##.

#####, ##### ## ## ## ##
#####. ## ##### ## ##, ##### ## ## ##—
##.

/etc/pam.d/ ## ## ## ## /etc/pam.conf, ## ## ## ##

##, ## ##, ##### ## ## ## ##.

3.1, #
#.

##—
3.3, # ##### ## ##### # ## ## ## ## ## ##

#####

#####. ##### ##### ## ##### ##### ## ##
#####; #####

##—
#####). ##### ## ##### ## ##### ## ##—
#####.

4.3.

#####, ## ## ##### ## #####
#####.

###_#####(3) ## ##### ## ##—
(### ##
#####). ## ## ## ##### ## ## ##, ## ##### ## ## ##—
other ## #####.

##, ##### ##### ## ## ## ##, ## ##—

#####. #####
##, ## ## ## ## ## ## ## ##
##. # ##### ##, ## ##
##, ## ## ## ##:

1. ##### ## ##

	PAM_SUCCESS	PAM_IGNORE	other
#####	## (!####) #####;	#	#### = ####;
#####	#	#	#### = ####;
#####	#	#	#### = ####, #####;
#####	## (!####) #####;	#	#
#####	#	#	#

fail ## ## ## ## ##, ## ##### ## ## ##, ## ##—

PAM_SUCCESS ## #####.

PAM_NEW_AUTHOK_REQD
##, #### ## ##### ##
PAM_NEW_AUTHOK_REQD ## #####
PAM_NEW_AUTHOK_REQD.

###_#####(3) ##### ## binding ## suffi-
cient ##### required.

#####

#####(3) ##### ## #####
#####(## #####) ##### ## ##
#####(##) ## ## ##### ## ##-
binding ## sufficient ##### required.

5.

5.1. #####(8)

#####(8) ##### ## #####; ## #-
PAM_AUTH_ERR. ## ##
#####(#####), ## ##
sufficient.

5.2. #####(8)

#####(8) ##### # ## ##-
PAM_TEXT_INFO. ## ##

##.

5.3. #####(8)

#####(8) ##### ## ## #-
####, ## ## ## ## ##
##-
##.

5.4. #####(8)

#####(8)

5.5. #####(8)

#####(8)

5.6. #####(8)

#####(8) ##### ## ## ##-
#####(##### wheel ##(1)). ## ## #-
##(1) #####

#####.

#####

5.15. ###_#####(8)

[###_#####\(8\)](#) ## ##### ## ##### #####; ##
PAM_SUCCESS. ## ##### ##-
#####.

5.16. ###_#####(8)

[###_#####\(8\)](#)

5.17. ###_#####(8)

[###_#####\(8\)](#)

5.18. ###_#####(8)

[###_#####\(8\)](#) ##### ## ##### ## #####
0. ##### ## ##
[##\(1\)](#) ## [#####\(1\)](#) ## ##### root #####
#####.

5.19. ###_#####(8)

[###_#####\(8\)](#)

5.20. ###_####(8)

[###_####\(8\)](#) ##### ## ##### ## ##
##. ## ## ## ##
[##\(1\)](#) ## ##### ## ##.

5.21. ###_###(8)

[###_###\(8\)](#)

5.22. ###_#####(8)

[###_#####\(8\)](#)

5.23. ###_####(8)

[###_####\(8\)](#) #####
##, ## [#####\(3\)](#) ##### ## ##
##. ## ## ##
(#####) #####
##. ##

#####

```
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR -
PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR -
CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE -
GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, -
STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
*
* $P4: -//depot/projects/openpam/bin/su/su.c#10 $
* $FreeBSD: head/fr_FR.ISO8859-1/articles/pam/su.c 38826 2012-05-17 19:12:14Z hrs $
*/

#include <sys/param.h>
#include <sys/wait.h>

#include <err.h>
#include <pwd.h>
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <syslog.h>
#include <unistd.h>

#include <security/pam_appl.h>
#include <security/openpam.h> /* for openpam_ttyconv() */

extern char **environ;

static pam_handle_t *pamh;
static struct pam_conv pamc;

static void
usage(void)
{
    fprintf(stderr, "-Usage: su [login [args]]\n");
    exit(1);
}

int
main(int argc, char *argv[])
{
    char hostname[MAXHOSTNAMELEN];
    const char *user, *tty;
    char **args, **pam_envlist, **pam_env;
    struct passwd *pwd;
    int o, pam_err, status;
```

```
pid_t pid;

while ((o = getopt(argc, argv, "-h")) != -1)
    switch (o) {
        case '-h':
        default:
            usage();
    }

argc -= optind;
argv += optind;

if (argc > 0) {
    user = *argv;
    --argc;
    ++argv;
} else {
    user = "-root";
}

/* initialize PAM */
pamc.conv = &openpam_ttyconv;
pam_start("su", user, &pamc, &pamh);

/* set some items */
gethostname(hostname, sizeof(hostname));
if ((pam_err = pam_set_item(pamh, PAM_RHOST, hostname)) != PAM_SUCCESS)
    goto pamerr;
user = getlogin();
if ((pam_err = pam_set_item(pamh, PAM_RUSER, user)) != PAM_SUCCESS)
    goto pamerr;
tty = ttyname(STDERR_FILENO);
if ((pam_err = pam_set_item(pamh, PAM_TTY, tty)) != PAM_SUCCESS)
    goto pamerr;

/* authenticate the applicant */
if ((pam_err = pam_authenticate(pamh, 0)) != PAM_SUCCESS)
    goto pamerr;
if ((pam_err = pam_acct_mgmt(pamh, 0)) == PAM_NEW_AUTHOK_REQD)
    pam_err = pam_chauthtok(pamh, PAM_CHANGE_EXPIRED_AUTHOK);
if (pam_err != PAM_SUCCESS)
    goto pamerr;

/* establish the requested credentials */
if ((pam_err = pam_setcred(pamh, PAM_ESTABLISH_CRED)) != PAM_SUCCESS)
    goto pamerr;

/* authentication succeeded; open a session */
if ((pam_err = pam_open_session(pamh, 0)) != PAM_SUCCESS)
    goto pamerr;

/* get mapped user name; PAM may have changed it */
pam_err = pam_get_item(pamh, PAM_USER, (const void **)&user);
```

#####

```
if (pam_err != PAM_SUCCESS || (pwd = getpwnam(user)) == NULL)
    goto pamerr;

/* export PAM environment */
if ((pam_envlist = pam_getenvlist(pamh)) != NULL) {
    for (pam_env = pam_envlist; *pam_env != NULL; ++pam_env) {
        putenv(*pam_env);
        free(*pam_env);
    }
    free(pam_envlist);
}

/* build argument list */
if ((args = calloc(argc + 2, sizeof *args)) == NULL) {
    warn("calloc()");
    goto err;
}
*args = pwd->pw_shell;
memcpy(args + 1, argv, argc * sizeof *args);

/* fork and exec */
switch ((pid = fork())) {
case -1:
    warn("fork()");
    goto err;
case 0:
    /* child: give up privs and start a shell */

    /* set uid and groups */
    if (initgroups(pwd->pw_name, pwd->pw_gid) == -1) {
        warn("initgroups()");
        _exit(1);
    }
    if (setgid(pwd->pw_gid) == -1) {
        warn("setgid()");
        _exit(1);
    }
    if (setuid(pwd->pw_uid) == -1) {
        warn("setuid()");
        _exit(1);
    }
    execve(*args, args, environ);
    warn("execve()");
    _exit(1);
default:
    /* parent: wait for child to exit */
    waitpid(pid, &status, 0);

    /* close the session and release PAM resources */
    pam_err = pam_close_session(pamh, 0);
    pam_end(pamh, pam_err);

    exit(WEXITSTATUS(status));
}
```

#####

```
}

pamerr:
    fprintf(stderr, -"Sorry\n");
err:
    pam_end(pamh, pam_err);
    exit(1);
}
```

#. #####

(8) #####
#####. #####
#####, #####
: ##### (3) #####
#####

```
/*-
 * Copyright (c) 2002 Networks Associates Technology, Inc.
 * All rights reserved.
 *
 * This software was developed for the FreeBSD Project by ThinkSec AS and
 * Network Associates Laboratories, the Security Research Division of
 * Network Associates, Inc. under DARPA/SPAWAR contract N66001-01-C-8035
 * ("CBOSS"), as part of the DARPA CHATS research program.
 *
 * Redistribution and use in source and binary forms, with or without
 * modification, are permitted provided that the following conditions
 * are met:
 * 1. Redistributions of source code must retain the above copyright
 *    notice, this list of conditions and the following disclaimer.
 * 2. Redistributions in binary form must reproduce the above copyright
 *    notice, this list of conditions and the following disclaimer in the
 *    documentation and/or other materials provided with the distribution.
 * 3. The name of the author may not be used to endorse or promote
 *    products derived from this software without specific prior written
 *    permission.
 *
 * THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
 * ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
 * IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR -
 * PURPOSE
 * ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
 * FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR -
 * CONSEQUENTIAL
 * DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE -
 * GOODS
 * OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
```

#####

```
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, -
STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
*
* $P4: -//depot/projects/openpam/modules/pam_unix/pam_unix.c#3 $
* $FreeBSD: head/fr_FR.ISO8859-1/articles/pam/pam_unix.c 38826 2012-05-17 19:12:14Z hrs $
*/

#include <sys/param.h>

#include <pwd.h>
#include <stdlib.h>
#include <stdio.h>
#include <string.h>
#include <unistd.h>

#include <security/pam_modules.h>
#include <security/pam_appl.h>

#ifndef _OPENPAM
static char password_prompt[] = "-Password:";
#endif

#ifndef PAM_EXTERN
#define PAM_EXTERN
#endif

PAM_EXTERN int
pam_sm_authenticate(pam_handle_t *pamh, int flags,
int argc, const char *argv[])
{
#ifndef _OPENPAM
struct pam_conv *conv;
struct pam_message msg;
const struct pam_message *msgp;
struct pam_response *resp;
#endif
struct passwd *pwd;
const char *user;
char *crypt_password, *password;
int pam_err, retry;

/* identify user */
if ((pam_err = pam_get_user(pamh, &user, NULL)) != PAM_SUCCESS)
return (pam_err);
if ((pwd = getpwnam(user)) == NULL)
return (PAM_USER_UNKNOWN);

/* get password */
#ifndef _OPENPAM
pam_err = pam_get_item(pamh, PAM_CONV, (const void **)&conv);
```

```

if (pam_err != PAM_SUCCESS)
    return (PAM_SYSTEM_ERR);
msg.msg_style = PAM_PROMPT_ECHO_OFF;
msg.msg = password_prompt;
msgp = &msg;
#endif
for (retry = 0; retry < 3; ++retry) {
#ifdef _OPENPAM
    pam_err = pam_get_authtok(pamh, PAM_AUTHTOK,
        (const char **)&password, NULL);
#else
    resp = NULL;
    pam_err = (*conv->conv)(1, &msgp, &resp, conv->appdata_ptr);
    if (resp != NULL) {
        if (pam_err == PAM_SUCCESS)
            password = resp->resp;
        else
            free(resp->resp);
        free(resp);
    }
#endif
    if (pam_err == PAM_SUCCESS)
        break;
    }
    if (pam_err == PAM_CONV_ERR)
        return (pam_err);
    if (pam_err != PAM_SUCCESS)
        return (PAM_AUTH_ERR);

    /* compare passwords */
    if ((!pwd->pw_passwd[0] && (flags & PAM_DISALLOW_NULL_AUTHTOK)) ||
        (crypt_password = crypt(password, pwd->pw_passwd)) == NULL ||
        strcmp(crypt_password, pwd->pw_passwd) != 0)
        pam_err = PAM_AUTH_ERR;
    else
        pam_err = PAM_SUCCESS;
#ifdef _OPENPAM
    free(password);
#endif
    return (pam_err);
}

PAM_EXTERN int
pam_sm_setcred(pam_handle_t *pamh, int flags,
    int argc, const char *argv[])
{
    return (PAM_SUCCESS);
}

PAM_EXTERN int
pam_sm_acct_mgmt(pam_handle_t *pamh, int flags,
    int argc, const char *argv[])

```

```
{
    return (PAM_SUCCESS);
}

PAM_EXTERN int
pam_sm_open_session(pam_handle_t *pamh, int flags,
    int argc, const char *argv[])
{
    return (PAM_SUCCESS);
}

PAM_EXTERN int
pam_sm_close_session(pam_handle_t *pamh, int flags,
    int argc, const char *argv[])
{
    return (PAM_SUCCESS);
}

PAM_EXTERN int
pam_sm_chauthtok(pam_handle_t *pamh, int flags,
    int argc, const char *argv[])
{
    return (PAM_SERVICE_ERR);
}

#ifdef PAM_MODULE_ENTRY
PAM_MODULE_ENTRY("pam_unix");
#endif
```


#####(3)#####.

#####,

#####(3)#####
#####

```
/*-
 * Copyright (c) 2002 Networks Associates Technology, Inc.
 * All rights reserved.
 *
 * This software was developed for the FreeBSD Project by ThinkSec AS and
```


###

```
* Network Associates Laboratories, the Security Research Division of
* Network Associates, Inc. under DARPA/SPAWAR contract N66001-01-C-8035
* ("CBOSS"), as part of the DARPA CHATS research program.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
* notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
* notice, this list of conditions and the following disclaimer in the
* documentation and/or other materials provided with the distribution.
* 3. The name of the author may not be used to endorse or promote
* products derived from this software without specific prior written
* permission.
*
* THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS" AND
* ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR -
PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE
* FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR -
CONSEQUENTIAL
* DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE -
GOODS
* OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
* HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, -
STRICT
* LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY
* OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
*
* $FreeBSD: head/fr_FR.ISO8859-1/articles/pam/converse.c 38826 2012-05-17 19:12:14Z hrs $
*/

#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>

#include <security/pam_appl.h>

int
converse(int n, const struct pam_message **msg,
struct pam_response **resp, void *data)
{
    struct pam_response *aresp;
    char buf[PAM_MAX_RESP_SIZE];
    int i;

    data = data;
    if (n <= 0 -|| n > PAM_MAX_NUM_MSG)
        return (PAM_CONV_ERR);
```


#####

```
if ((aresp = calloc(n, sizeof *aresp)) == NULL)
    return (PAM_BUF_ERR);
for (i = 0; i < n; ++i) {
    aresp[i].resp_retcode = 0;
    aresp[i].resp = NULL;
    switch (msg[i]->msg_style) {
    case PAM_PROMPT_ECHO_OFF:
        aresp[i].resp = strdup(getpass(msg[i]->msg));
        if (aresp[i].resp == NULL)
            goto fail;
        break;
    case PAM_PROMPT_ECHO_ON:
        fputs(msg[i]->msg, stderr);
        if (fgets(buf, sizeof buf, stdin) == NULL)
            goto fail;
        aresp[i].resp = strdup(buf);
        if (aresp[i].resp == NULL)
            goto fail;
        break;
    case PAM_ERROR_MSG:
        fputs(msg[i]->msg, stderr);
        if (strlen(msg[i]->msg) > 0 &&
            msg[i]->msg[strlen(msg[i]->msg) - 1] != '\n')
            fputc('\n', stderr);
        break;
    case PAM_TEXT_INFO:
        fputs(msg[i]->msg, stdout);
        if (strlen(msg[i]->msg) > 0 &&
            msg[i]->msg[strlen(msg[i]->msg) - 1] != '\n')
            fputc('\n', stdout);
        break;
    default:
        goto fail;
    }
}
*resp = aresp;
return (PAM_SUCCESS);
fail:
    for (i = 0; i < n; ++i) {
        if (aresp[i].resp != NULL) {
            memset(aresp[i].resp, 0, strlen(aresp[i].resp));
            free(aresp[i].resp);
        }
    }
    memset(aresp, 0, n * sizeof *aresp);
    *resp = NULL;
    return (PAM_CONV_ERR);
}
```


#####

#####

#####

[1] *Rendre les services de connexion indépendants des technologies d'authentification* .
#####

[2] *X/Open Single Sign-on Preliminary Specification*. ### 1#85912#144#6.
1997.

[3] *Pluggable Authentication Modules*. #####. 1999#10#06.

#####

[4] *Administration de PAM* . #####.

#####

[5] *La page d'OpenPAM*. #####.

[6] *La page de Linux-PAM*. #####.

[7] *La page de Solaris PAM*. #####.